1-967325-2 - ACTIVE

TE Internal #: 1-967325-2 Housing for Female Terminals, Wire-to-Wire, 4 Position, .276 in [7 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging) View on TE.com >



Connectors > Automotive Connectors > Connector Housings > CIRCULAR DIN HOUSINGS



Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 2.5 mm [.098 in]

Connector System: Wire-to-Wire

Number of Positions: **4**

Centerline (Pitch): 7 mm [.276 in]

All CIRCULAR DIN HOUSINGS (51)

Features

Product Type Features

Connector & Housing Shape	Circular	
Connector & Housing Type	Housing for Female Terminals	
Connector System	Wire-to-Wire	
Sealable	Yes	
Hybrid Connector	No	
Primary Locking Feature	On the Terminal	
Configuration Features		
Blank Cavity Position	4	
Number of Positions	4	
Electrical Characteristics		
Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V	
Body Features		
Cable Exit Angle	180°	

Housing for Female Terminals, Wire-to-Wire, 4 Position, .276 in [7 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging)



Body Material	Other	
Primary Product Color	Black	
Connector Code	1	
Contact Features		
Contact Size	2.5mm	
Contact Type	Socket	
Mating Pin Diameter	2.5 mm[.098 in]	
Mechanical Attachment		
Mounting Feature	Without	
Terminal Position Assurance	No	
Strain Relief	Without	
Mating Alignment Type	Keyed	
Mating Alignment	With	
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Centerline (Pitch)	7 mm[.276 in]	

Dimensions

Product Length	31 mm[1.22 in]	
Product Height	32.8 mm[1.291 in]	
Usage Conditions		
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 ° F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]	
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]	
Industry Standards		
Degree of Protection	IP69K	
UL Flammability Rating	UL 94HB	
Packaging Features		
Packaging Quantity	500	
Packaging Method	Box	
Other		
Serviceable	No	

Housing for Female Terminals, Wire-to-Wire, 4 Position, .276 in [7 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging)



Connector Position Assurance Capable

No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not applicable for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Housing for Female Terminals, Wire-to-Wire, 4 Position, .276 in [7 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging)





Customers Also Bought



ABDECKKAPPE 90GRD	JPT REC 2.8 Contact SRC Au	SOC CONN CVRASSY,2POS, AMPSEAL16,90DEG,MC	TAT-125-1/4-0-1IN
ETE			
TE Part #330301-3 TERMINAL,SOLIS, R, 2, M5	TE Part #6-1355512-7 47 WAY ABS CONNECTOR		

Documents

Product Drawings 2,5MM BU-GEH 3P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-967325-2_E_c-1-967325-2-e.2d_dxf.zip

Housing for Female Terminals, Wire-to-Wire, 4 Position, .276 in [7 mm] Centerline, Sealable, Black, Cable Mount (Free-Hanging)



English

Customer View Model ENG_CVM_CVM_1-967325-2_E_c-1-967325-2-e.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-967325-2_E_c-1-967325-2-e.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages CONNECTOR SELECTOR

English

Product Specifications Product Specification

English

Product Environmental Compliance Product Compliance

English

Product Compliance

English