




DO NOT SCALE DRAWING	 www.fciconnect.com	 ISO PROJECTION SCALE 5:1
TITLE Terminal 2.8 DCK Female		DIMENSION IN MILLIMETERS DWG SIZE A3
CATALOG NUMBER --	 SHEET 1 of 1	THIS DRAWING AND ALL OTHER INFORMATION CONTAINED THEREIN IS PROPRIETARY AND THE PROPERTY OF FCI. This drawing may not be copied, reproduced or disclosed to any third party without the expressed written permission of FCI. © FCI April 1999

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60013631](#)

[Assistant](#)



60013631

DCK female 2.8 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Mating Half

[60110331](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	2.8
Family	DCK
Features	Suitable for Secondary Lock Long Box in CrNi

Dimensional

Contact Pitch	5 mm
---------------	------

Electrical

Current Carrying Capacity at 23°C	30A
Current Carrying Capacity at 85°C	20A
Current Carrying Capacity at 100°C	15A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 3

Mechanical

Range of Wire Gauge Min - Max	0.5 - 1 mm ²
Contact mating force	< 9N
Single Wire Seal Compatible	No
Contact unmating force	< 5N

Physical

Plating	Sn
Material	CuNiSi/CrNi

Environmental

IMDS	No
------	----

Other Features

Type	Female
Crimping Tool	65200715
Tradename	DCK
Disclaimer	<p>Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.</p>

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60013641](#)

[Assistant](#)



60013641

DCK female 2.8 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Mating Half

[60110341](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	2.8
Family	DCK
Features	Suitable for Secondary Lock Long Box in CrNi

Dimensional

Contact Pitch	5 mm
---------------	------

Electrical

Current Carrying Capacity at 23°C	30A
Current Carrying Capacity at 85°C	20A
Current Carrying Capacity at 100°C	15A
Maximum Insulation (in mm)	3
Resistance (Contact)	< 3

Mechanical

Range of Wire Gauge Min - Max	1 - 2.5 mm ²
Contact mating force	< 9N
Single Wire Seal Compatible	No
Contact unmating force	< 5N

Physical

Plating	Sn
Material	CuNiSi/CrNi

Environmental

IMDS	No
------	----

Other Features

Type	Female
Crimping Tool	65200716
Tradename	DCK
Disclaimer	<p>Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.</p>

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60013711](#)

[Assistant](#)



60013711

DCK female 2.8 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Mating Half

[60110511](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	2.8
Family	DCK
Features	Suitable for Secondary Lock Long Box in CrNi

Dimensional

Contact Pitch	6 mm
---------------	------

Electrical

Current Carrying Capacity at 23°C	30A
Current Carrying Capacity at 85°C	20A
Current Carrying Capacity at 100°C	15A
Maximum Insulation (in mm)	1.4
Resistance (Contact)	< 3

Mechanical

Range of Wire Gauge Min - Max	0.22 - 0.35 mm2
Contact mating force	< 9N
Single Wire Seal Compatible	Yes
Contact unmating force	< 5N

Physical

Plating	Sn
Material	CuNiSi/CrNi

Environmental

IMDS	No
------	----

Other Features

Type	Female
Crimping Tool	65200717
Tradename	DCK
Disclaimer	<p>Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.</p>

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60013731](#)

[Assistant](#)



60013731

DCK female 2.8 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Mating Half

[60110531](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	2.8
Family	DCK
Features	Suitable for Secondary Lock Long Box in CrNi

Dimensional

Contact Pitch	6 mm
---------------	------

Electrical

Current Carrying Capacity at 23°C	30A
Current Carrying Capacity at 85°C	20A
Current Carrying Capacity at 100°C	15A
Maximum Insulation (in mm)	21
Resistance (Contact)	< 3

Mechanical

Range of Wire Gauge Min - Max	0.5 - 1 mm2
Contact mating force	< 9N
Single Wire Seal Compatible	Yes
Contact unmating force	< 5N

Physical

Plating	Sn
Material	CuNiSi/CrNi

Environmental

IMDS	No
------	----

Other Features

Type	Female
Tradename	DCK
Disclaimer	<p>Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.</p>

- Direct Links**
 - Cross Reference
 - RoHS/LF P/N search
 - Document & Drawing search
 - Application tooling
- Services**
 - Contact us
 - Distributor list
 - Pricing request
 - Order samples
- Literature**
 - Brochures & catalogs
 - Product documentation
 - Technical library

[Back > 60013741](#)

[Assistant](#)



60013741

DCK female 2.8 mm terminal

ACTIVE

[Customer Drawing](#)

Automotive division

[Email Datasheet](#) [Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- € [Price request](#)

Mating Half

[60110541](#)

Specifications

General Dimensional Electrical Mechanical Physical Environmental **Other Features**

General

Product Type	Terminal System
Terminal size (in mm)	2.8
Family	DCK
Features	Suitable for Secondary Lock Long Box in CrNi

Dimensional

Contact Pitch	6 mm
---------------	------

Electrical

Current Carrying Capacity at 23°C	30A
Current Carrying Capacity at 85°C	20A
Current Carrying Capacity at 100°C	15A
Maximum Insulation (in mm)	3
Resistance (Contact)	< 3

Mechanical

Range of Wire Gauge Min - Max	1 - 2.5 mm ²
Contact mating force	< 9N
Single Wire Seal Compatible	Yes
Contact unmating force	< 5N

Physical

Plating	Sn
Material	CuNiSi/CrNi

Environmental

IMDS	No
------	----

Other Features

Type	Female
Tradename	DCK
Disclaimer	<p>Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.</p>