TE Internal #: 179631-1

Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 185 °F [-40

-85 °C]

View on TE.com >



Connectors > Automotive Connectors > Connector Housings











Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.5 mm [.059 in]

Connector System: Wire-to-Wire

Number of Positions: 16

Centerline (Pitch): 2.2 mm [.086 in]

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	No
Configuration Features	
Number of Positions	16
Number of Rows	2
Body Features	
Cable Exit Angle	180°
Body Material	PBT

Primary Product Color

Contact Size	1.5mm	

Natural



Contact Type	Receptacle
Mating Tab Width	1.5 mm[.059 in]
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	2.2 mm[.086 in]
Dimensions	
Product Width	21.2 mm[.834 in]
Product Length	49.2 mm[1.93 in]
Product Height	26.2 mm[1.03 in]
Row-to-Row Spacing	8.6 mm[.339 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C[158 °F][167 °F] [176 °F][185 °F]
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	50
Packaging Method	Bag
Other	
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



















TE Part #5-1897638-5 C.E BOX ASSY-BLM F/L-1FAN,4PW, STD

Documents

Product Drawings

DIAGNOSTIC PLUG HSG 16P NARU.

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_179631-1_N.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_179631-1_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_179631-1_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Housing for Female Terminals, Wire-to-Wire, 16 Position, .086 in [2.2 mm] Centerline, Natural, Signal, Panel Mount, -40 – 185 °F [-40 – 85 °C]



Instruction Sheets

Instruction Sheet (U.S.)

English

Automotive On-Board Diagnostic Connector 179631-1

English