

175024-1 ✓ ACTIVE

Positive Lock | Positive Lock 250


TE Internal #: 175024-1

Quick Disconnects, Receptacle, 15 – 10 AWG Wire Size, 1.65 – 5.26 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Straight, Brass, Positive Lock 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: 1.65 – 5.26 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

Terminates To	Wire & Cable
Wire Stop	No
Wire/Cable Type	Regular Wire
Sealable	No

Configuration Features

Connection Capacity	Single
---------------------	--------

Electrical Characteristics

Voltage (Max)	250 V
---------------	-------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm [.25 in]
Mating Tab Thickness	.81 mm [.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass



Terminal Plating Material	Pre-Tin
---------------------------	---------

Crimp Type	F-Crimp
------------	---------

Barrel Type	Open
-------------	------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Accepts Wire Insulation Diameter Range	3 – 5.1 mm [.118 – .2 in]
--	---------------------------

Overall Length	21.2 mm [.834 in]
----------------	-------------------

Receptacle Terminal Stock Thickness	.41 mm [.016 in]
-------------------------------------	------------------

Wire Size	1.65 – 5.26 mm ²
-----------	-----------------------------

Usage Conditions

Insulation Option	Fully Insulated
-------------------	-----------------

Operating Temperature Range	-40 – 110 °C [-40 – 230 °F]
-----------------------------	-----------------------------

Packaging Features

Packaging Quantity	4000
--------------------	------

Packaging Method	Strip/Reel
------------------	------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
--	---

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	---

Solder Process Capability	Not applicable for solder process capability
---------------------------	--

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2232343-1
250 PL EX FLAG REC. 18-12AWG PTBR



TE Part # 175022-2
250 POSITIVE REC EX MK-2



TE Part # 2-2150062-2
OCEAN_2.0_Applicator-E-150F220F



TE Part # 2150062-2
OCEAN_2.0_Applicator-E-150F220F



TE Part # 2232343-2
250 PL EX FLAG REC. 18-12AWG
PTBR FLAT



TE Part # 2376579-2
250 FASTON PCB TAB TPBR



TE Part # 2376582-2
250 FASTON PCB TAB TPBR



TE Part # 2376591-2
250 FASTON PCB TAB TPBR



TE Part # 2376595-2
250 FASTON PCB TAB TPBR




TE Part # 2391865-1
POSITIVE LOCK 250 (6.3 MM) SLEEVE




TE Part # 2391865-2
250 sleeve PL YELLOW transparent




TE Part # 7-2150062-2
OCEAN_2.0_Applicator-E-150F220F



TE Part # 7-2150062-7
OCEAN_2.0_SPARE_PART_KIT-
150F220F



TE Part # 174817-1
POSITIVE LOCK 250 (6.3 MM) SLEEVE



TE Part # 174817-2
250 sleeve PL YELLOW transparent




TE Part # 2376591-3
250 FASTON PCB TAB TPBR LP

Also in the Series | **Positive Lock 250**



Automotive Terminals(1)




Crimp Terminal Housings(203)



Insertion & Extraction Tools(3)






Insulation Boots & Sleeves(4)



Quick Disconnects(189)

Customers Also Bought

TE Part #1376393-1
5MM POWER KEY 6P PLUG HSG NUTTE Part #179861-1
AMP POWER D/LOCK PLUG HSG 4PTE Part #175057-2
250 PL EX FLAG REC. 18-12AWG PTBRTE Part #175178-1
PL EX 250 REC TERMINAL-FLAG 12-10 PTPBTE Part #170338-1
AMP-IN 22-18 AWGTE Part #3-292236-0
1.5 MINI CT DC DRAWER REC ASSYTE Part #176271-6
AMP UNIVERSAL POWER PLUG 2P

Documents

Product Drawings

[250 PL EX REC. 15-10AWG PTBR](#)

Japanese

CAD Files

Customer View Model

[ENG_CVM_CVM_175024-1_G.2d_dxf.zip](#)

English

[3D PDF](#)



3D

Customer View Model

[ENG_CVM_CVM_175024-1_G.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_175024-1_G.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_175024-1_053120182141_dmtec](#)

English

[MD_175024-1_053120182141_dmtec](#)

English

Instruction Sheets

[Instruction Sheet \(non U.S.\)](#)

English

[POSITIVE LOCK EX CONTACT](#)

English

Agency Approvals

[Agency Approval Document](#)

English