1924212-1 ✓ ACTIVE

Generation Y Connector System

TE Internal #: 1924212-1


Housing for Male Terminals, Wire-to-Wire, 6 Position, .1 in [2.54 mm] Centerline, Sealable, Gray, Signal, Generation Y Connector

System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings



Connector & Housing Type: Housing for Male Terminals

Mating Tab Width: .64 mm [.025 in]

Connector System: Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 2.54 mm [.1 in]

Features

Product Type Features

Troduct Type readures	
Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	6
Number of Rows	2
Body Features	

Cable Exit Angle	180°
Body Material	PA GF
Primary Product Color	Gray
Connector Code	В

Contact Features

Contact Size	.64mm
Contact Type	Tab
Mating Tab Width	.64 mm[.025 in]



Mechanical Attachment

Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Product Width	20.45 mm[.805 in]
Product Length	46.55 mm[1.833 in]
Product Height	22.74 mm[.895 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Usage Conditions	
	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Usage Conditions	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230
Usage Conditions Operating Temperature (Max)	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Usage Conditions Operating Temperature (Max) Operating Temperature Range	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Usage Conditions Operating Temperature (Max) Operating Temperature Range Operation/Application	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F] -40 – 125 °C[-40 – 257 °F]
Usage Conditions Operating Temperature (Max) Operating Temperature Range Operation/Application Circuit Application	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 ° F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F] -40 – 125 °C[-40 – 257 °F]
Usage Conditions Operating Temperature (Max) Operating Temperature Range Operation/Application Circuit Application Packaging Features	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F] -40 – 125 °C[-40 – 257 °F] Signal
Usage Conditions Operating Temperature (Max) Operating Temperature Range Operation/Application Circuit Application Packaging Features Packaging Quantity	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F] -40 - 125 °C[-40 - 257 °F] Signal
Usage Conditions Operating Temperature (Max) Operating Temperature Range Operation/Application Circuit Application Packaging Features Packaging Quantity Packaging Method	105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F] -40 - 125 °C[-40 - 257 °F] Signal

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | Generation Y Connector System




Automotive Connector Caps & Covers (16)



Automotive Housings(153)



Automotive Terminals(39)



Insertion & Extraction Tools(1)





Customers Also Bought













Documents

Product Drawings

ASSY, CAP, 2X3, SEALED, 0.64, OPEN

English

CAD Files

Customer View Model

ENG_CVM_1924212-1_B1.3d_igs.zip

English

Customer View Model

ENG_CVM_1924212-1_B1.3d_stp.zip

English

Customer View Model

ENG_CVM_1924212-1_B1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Housing for Male Terminals, Wire-to-Wire, 6 Position, .1 in [2.54 mm] Centerline, Sealable, Gray, Signal, Generation Y Connector System



Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (U.S.)

English