

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

--

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION	DATE	DWN	APVD	
J	-	R		REDRAWN W/CHANGE	ECR-16-000305	08JAN2016	TS	KB

① TO BE MEASURED BETWEEN -A- AND 2mm
 ② TO BE MATES WITH PLUG HOUSING SMOOTHLY.
 3. APPLICABLE CONTACT NO. 172773, 172775, ETC.
 4. PRODUCT SPEC NO.: 108-5165, 108-5166
 5. IN COUPLING WITH PLUG HOUSING 29.4N (3kg) MAX. WITHOUT RECEPTACLE CONTACT.

① -A- 面より2mmの範囲で測定
 ② 相手ハウジングと所定の機能を満たして嵌合できること。
 3. 内装するリセパタクルコンタクトは型番172773, 172775 他。
 4. 製品規格: 108-5165, 108-5166
 5. 相手ハウジングとの嵌合力は29.4N (3kg) 以下。但しリセパタクルコンタクトは含まない。

	YELLOW	172495-7
	GRAY	172495-6
	BLUE	172495-5
OBSOLETE	GREEN	172495-4
	BROWN	172495-3
	BLACK	172495-2
	NATURAL	172495-1
	COLOR	PART NUMBER

TOLERANCE UNLESS OTHERWISE SPECIFIED:
一般公差

0 < x ≤ 10	: ±0.2
10 < x ≤ 30	: ±0.25
30 < x ≤ 100	: ±0.3
ANGLE ; 角度	: ±3°

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		TE Connectivity	
mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		T. SHINOHARA		08JAN2016	
		0 PLC ± -		CHK		08JAN2016	
		1 PLC ± -		K.BETSUI			
MATERIAL		2 PLC ± -		APVD		08JAN2016	
		3 PLC ± -		K.BETSUI			
NYLON		4 PLC ± -		PRODUCT SPEC		NAME	
		ANGLES ± -		SEE NOTE		MULTI INTER LOCK CONNECTOR MK-II	
FINISH		-		APPLICATION SPEC		7 POSITION PLUG HOUSING	
-		-		-		RESTRICTED TO	
-		-		WEIGHT		-	
-		-		CUSTOMER DRAWING		SCALE 2:1 SHEET 1 of 1 REV R	

1470-19 (3/11)