AMP | Sealed Sensor Connector SSC System

TE Internal #: 184060-1


Housing for Female Terminals, Wire-to-Device / Wire-to-Wire / Wire-to-Board, 6 Position, .197 in [5 mm] Centerline, Sealed Sensor

Connector SSC System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings



Connector & Housing Type: Housing for Female Terminals

Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 5 mm [.197 in]

Sealable: Yes

Features

Product Type Features

Connector & Housing Type Connector System Wire-to-Board, Wire-to-Device, Wire-to-Wire Sealable Yes Hybrid Connector No Primary Locking Feature Integrated in Housing Configuration Features Number of Positions Number of Rows 1 Electrical Characteristics Operating Voltage Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle Body Material PA GF Primary Product Color Wire-to-Board, Wire-to-Device, Wire-to-Wir	Connector & Housing Shape	Rectangular
Sealable Yes Hybrid Connector No Primary Locking Feature Integrated in Housing Configuration Features Number of Positions 6 Number of Rows 1 Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle 180° Body Material PA GF	Connector & Housing Type	Housing for Female Terminals
Hybrid Connector Primary Locking Feature Integrated in Housing Configuration Features Number of Positions 6 Number of Rows 1 Electrical Characteristics Operating Voltage Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle Body Material No Integrated in Housing 1 1 2 4 4 5 6 7 8 7 8 8 8 8 9 8 9 8 9 9 9 9 9 9 9 9 9	Connector System	
Primary Locking Feature Configuration Features Number of Positions 6 Number of Rows 1 Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle Body Material PA GF	Sealable	Yes
Configuration Features Number of Positions 6 Number of Rows 1 Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle 180° Body Material PA GF	Hybrid Connector	No
Number of Positions 6 Number of Rows 1 Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle Body Material PA GF	Primary Locking Feature	Integrated in Housing
Number of Rows 1 Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle 180° Body Material PA GF	Configuration Features	
Electrical Characteristics Operating Voltage 125 VAC Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle 180° Body Material PA GF	Number of Positions	6
Operating Voltage Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle Body Material PA GF	Number of Rows	1
Nominal Voltage Architecture 12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V Body Features Cable Exit Angle 180° Body Material PA GF	Electrical Characteristics	
Body Features Cable Exit Angle Body Material PA GF	Operating Voltage	125 VAC
Cable Exit Angle Body Material PA GF	Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V
Body Material PA GF	Body Features	
,	Cable Exit Angle	180°
Primary Product Color Black	Body Material	PA GF
	Primary Product Color	Black

А

Connector Code



Contact Features

Contact Size	1.8mm
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Product Width	27.6 mm[1.087 in]
Product Length	43.2 mm[1.7 in]
Product Height	24.8 mm[.98 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	800
Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





















TE Part # 184004-1 2 POS. PLUG ASSY, KEY C, BLACK



TE Part # 184165-1 2 POS. CAP HSG., KEY C



TE Part # 184022-1 2 POS. PLUG ASSY, KEY M, BLACK



TE Part # 184175-1 2 POS. CAP LP



TE Part # 184000-1 2 POS. PLUG ASSY, KEY A, BLACK



TE Part # 184012-1 2 POS. PLUG ASSY, KEY G, GRAY



TE Part # 184030-3 RECPT, CONTACT 070, PTPPHBZ



TE Part # 184002-1 2 POS. PLUG ASSY, KEY B, GRAY



TE Part # 184452-1 6 POS SSC PLUG ASSY, BLKD CKTS



TE Part # 184030-1 RECPT, CONTACT 070, AUPHBZ



TE Part # 184288-1 TRW E9DB-14A163-CA



TE Part # 184141-1 WIRE SEAL, RUBBER, SENSOR, PURPLE, LIM

Also in the Series | Sealed Sensor Connector SSC System



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(6)



Automotive Housings(178)



Automotive Seals & Cavity Plugs(3)



Automotive Terminals(8)




Insertion & Extraction Tools(1)




Other Automotive Connector Accessories(7)

Customers Also Bought



















TE Part #1939938-1 0.50/1.0 SEALED PLUG ASSY 60POS TE Part #1827483-1

Documents

Product Drawings

6 POS./6 CIRC PLUG ASSY, KEY A

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_184060-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_184060-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_184060-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Housing for Female Terminals, Wire-to-Device / Wire-to-Wire / Wire-to-Board, 6 Position, .197 in [5 mm] Centerline, Sealed Sensor Connector SSC System



Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Positioning the Double Lock Plate

English