

AMP | Timer Connector System

TE Internal #: 284716-4


Housing for Female Terminals, Wire-to-Board / Wire-to-Wire / Wire-to-Device, 6 Position, .157 in [4 mm] Centerline, Sealable, Timer

Connector System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > TIMER, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.5 mm [.059 in]

Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 4 mm [.157 in]

All TIMER, CONNECTOR HOUSING (543)

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device, Wire-to- Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	6
Number of Rows	2
Electrical Characteristics	
Operating Voltage	24 VDC
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	180°
Body Material	PA GF
Primary Product Color	Black



Contact Features

Contact Size	1.5mm
Contact Type	Receptacle
Mating Tab Width	1.5 mm[.059 in]

Mechanical Attachment

Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Dimensions

Product Width	24.2 mm[.953 in]
Product Length	29.4 mm[1.157 in]
Product Height	30.3 mm[1.193 in]
Row-to-Row Spacing	5 mm[.197 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F]
Operating Temperature Range	-40 - 140 °C[-40 - 284 °F]

Operation/Application

Circuit Application	Signal	

Packaging Features

Other

Serviceable	Yes
Connector Position Assurance Capable	Yes

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts










TE Part # 2362453-1 CT,HARNESS,WEICHAI BOSCH WP13 EURP VI



Also in the Series | Timer Connector System



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(16)



Automotive Housings(219)



Automotive Seals & Cavity Plugs(31)



Automotive Terminals(140)



Crimp Terminal Housings(13)



Insertion & Extraction Tools(20)



Other Automotive Connector Accessories(1)



PCB Headers & Receptacles(78)



Quick Disconnects(4)

Customers Also Bought



TE Part #3-1534903-5 60POS MIXED MQS REC SEALED COD 2-3-6-7



TE Part #1924396-1 14P MCON 1.2 SCCM Inner Housing



TE Part #2098067-7 Plug Assembly, Hybrid, BCM, CL, G Key



TE Part #1-2208720-1 105POS,MCON 1.2 CB,REC HSG, ASSY,SLD



TE Part #2133662-1 REC CONN CVR ASSY,64POS,MQS





TE Part #1123653-1 .040 3 UNSEALED CONT.REC MS

TE Part #2208714-1
2. LOCK,MCON1,2 CB



TE Part #2819105-1 HSG FEMALE ASSY 64 WAYS

TE Part #2332444-1 DT04-3P-EP10-120,RECEPTACLE ASM-BLACK

Documents

Product Drawings

6 P. REC CONN X UEGO CONN

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_284716-4_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_284716-4_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_284716-4_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Timer Interconnection System

English

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (non U.S.)

English