

# Aptiv Connection Systems Catalog

[Customer Service](#) [Samples Request](#)

[Find by Feature](#) [Browse by Category](#) [Browse by Application](#)

[Comparison List \(0\)](#) [Share](#)

211CC2S1190P

Enter part number or keyword

[Search Results \(1\)](#) [Search Options](#)

1 Result(s): [ All ] - 211CC2S1190P

[Compare](#)

211CC2S1190P - Sicma3 1.5 Female Unsealed Tin Plating Terminal Assembly, Cable Range 0.35 - 0.70 mm2

[Compare](#)

« ‹ 1 › »

## Sicma3 1.5 Female Unsealed Tin Plating Terminal Assembly, Cable Range 0.35 - 0.70 mm2

Part # 211CC2S1190P



[Question about this product?](#)

[Attributes](#) [Documents \(1\)](#)

<b>Part # :</b>	211CC2S1190P
<b>Description :</b>	Sicma3 1.5 Female Unsealed Tin Plating Terminal Assembly, Cable Range 0.35 - 0.70 mm2
<b>Product Type :</b>	Terminal
<b>Status :</b>	Active
<b>Blade size [mm] :</b>	1.5
<b>Series :</b>	1.5
<b>Gender :</b>	Female
<b>Sealable :</b>	Unsealed
<b>Material :</b>	CuCrAgFeTiSi
<b>Weight [g] :</b>	1
<b>Plating :</b>	Tin
<b>Maximum Cable Diameter [mm] :</b>	1.70
<b>Minimum Cable Core Cross Section [mm2] :</b>	0.35
<b>Maximum Cable Core Cross Section [mm2] :</b>	0.50
<b>Remarks :</b>	Former FCI Product, Delphi PN:13602481,SICMA 150 designed for high vibrations and temperature up to 145 °C, being fully compatible with previous SICMA Female terminals, One piece construction, High current carrying capacity, Low contact mating force, Suitable for secondary lock

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.