DT04-6P-CL09 ACTIVE

DEUTSCH | DEUTSCH DT

TE Internal #: DT04-6P-CL09

Housing for Male Terminals, Wire-to-Wire, 6 Position, .359 in [9.12 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal,

DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DT Series Housings & Connectors



Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 9.12 mm [.359 in]

All DEUTSCH DT Series Housings & Connectors (461)

Features

Product Type Features

| Connector & Housing Shape | Rectangular |
|-----------------------------------|----------------------------|
| Connector & Housing Type | Housing for Male Terminals |
| Connector System | Wire-to-Wire |
| Sealable | Yes |
| Hybrid Connector | No |
| Primary Locking Feature | Integrated in Housing |
| Connector & Contact Terminates To | Wire & Cable |

Configuration Features

| Blank Cavity Position | 0 |
|------------------------|------------------------|
| Connector Modification | Sealed Flange, End Cap |
| Number of Positions | 6 |
| Number of Rows | 3 |

Electrical Characteristics

| Operating Voltage | 250 VAC |
|------------------------------|------------------|
| Nominal Voltage Architecture | 12 V, 24 V, 48 V |

Body Features

| Cable Exit Angle | 180° | |
|------------------|------|--|



| Body Material | PA GF |
|--|------------------------------------|
| Primary Product Color | Black |
| Contact Features | |
| Contact Size | Size 16 |
| Contact Type | Pin |
| Mating Pin Diameter | 1.59 mm[.063 in] |
| Contact Current Rating (Max) | 13 A |
| Mechanical Attachment | |
| Mounting Feature | With |
| Terminal Position Assurance | Yes |
| Strain Relief | Add By Accessory |
| Mating Alignment Type | Polarized |
| Mating Alignment | With |
| Connector Mounting Type | Panel Mount |
| Housing Features | |
| Centerline (Pitch) | 9.12 mm[.359 in] |
| Dimensions | |
| Product Width | 30.99 mm[1.22 in] |
| Product Length | 47.45 mm[1.868 in] |
| Product Height | 54.74 mm[2.155 in] |
| Row-to-Row Spacing | 4.45 mm[.175 in] |
| Accepts Wire Insulation Diameter Range | 1.35 – 3.05 mm[.053 – .12 in] |
| Usage Conditions | |
| Operating Temperature (Max) | 125 °C[257 °F] |
| Operating Temperature Range | -55 – 125 °C[-67 – 257 °F] |
| Operation/Application | |
| Circuit Application | Power & Signal |
| Industry Standards | |
| Agency/Standard | SAE J2030 |
| Degree of Protection | IP68, IP6K9K |
| UL Flammability Rating | 12mm Flame Test per Standard UL-94 |
| | |



Packaging Features

| Packaging Quantity | 200 |
|--------------------|-----|
| Packaging Method | Box |

Other

| Serviceable | Yes |
|--------------------------------------|-----|
| Connector Position Assurance Capable | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-D48-SP729 DEUTSCH SEALING PLUGS



TE Part # CAT-D48-ST273 **DEUTSCH SOLID CONTACTS**



TE Part # 776364-1 SEALING PLUG, SZ 20 CAVITY



EXT TOOL, FRONT RELEASE

CONTACTS



TE Part # CAT-D487-CH8172 DEUTSCH DT Series Housings & Connectors



TE Part # DT6P-DC PROTECT CVR, 6P, REC, GRY, DT



TE Part # W6P WEDGE LOCK, 6P, REC, GRN, DT



Also in the Series | DEUTSCH DT





Automotive Connector Locks & Position Assurance(73)






Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

Customers Also Bought









07/07/2022 04:17AM | Page 4







TE Part #44061-3P HERM RECP

TE Part #GAG15K3D6 GLS2-GLASS PROBE

TE Part #GAG15K3D8 GLS2-GLASS PROBE

Documents

Product Drawings

REC, 6P, BLK, E, CAP, FLANGE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT04-6P-CL09_99_c-dt04-6p-cl09-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT04-6P-CL09_99_c-dt04-6p-cl09-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT04-6P-CL09_99_c-dt04-6p-cl09-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

Housing for Male Terminals, Wire-to-Wire, 6 Position, .359 in [9.12 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal, DEUTSCH DT



English

Product Compliance

English

Agency Approvals

UL Report

English