

### AMP | Multilock Connector System

TE Internal #: 917981-2

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 16


Position, .118 in [3 mm] Centerline, Black, Signal, Multilock

Connector System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > MULTILOCK, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1 mm [.039 in]

Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 16

Centerline (Pitch): 3 mm [.118 in]

### All MULTILOCK, CONNECTOR HOUSING (576)

### **Features**

# **Product Type Features**

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board, Wire-to-Device
Sealable	No
Hybrid Connector	Yes
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	16
Number of Rows	2
Electrical Characteristics	
Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V
Body Features	
Cable Exit Angle	180°
Body Material	PBT

Black

Primary Product Color



#### **Contact Features**

Contact Size	1.8mm, 1mm
Contact Type	Receptacle
Mating Tab Width	1 mm[.039 in]

### Mechanical Attachment

Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

# **Housing Features**

Centerline (Pitch)	3 mm[.118 in]
--------------------	---------------

#### **Dimensions**

Product Width	25 mm[.984 in]
Product Length	21 mm[.827 in]
Product Height	17.3 mm[.681 in]
Row-to-Row Spacing	5.2 mm[.205 in]

# **Usage Conditions**

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]

# Operation/Application

Circuit Application	Signal	
	9.19.1.6.1	

# **Industry Standards**

UL Flammability Rating	UL 94HB	
------------------------	---------	--

# Packaging Features

Packaging Quantity	100
Packaging Method	Bag

# Other

Serviceable	Yes	
-------------	-----	--



Connector Position Assurance Capable

No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts




























# Also in the Series | Multilock Connector System







Position Assurance(2)





Automotive Seals & Cavity Plugs(2)



Automotive Terminals(141)



Insertion & Extraction Tools(6)



Other Automotive Connector Accessories(9)



# Customers Also Bought





E TE

Sississis = TE

TE Part #1326032-9 1.5/2.8 CONNECTOR SYSTEM, RECPT AND TAB


TE Part #2035363-1 1X6 GENERATION Y ASSY KEY B

TE Part #2098216-1 32P Carrier, GY

TE Part #1924136-2 Carrier, 26P Generation Y, 52P Conn




TE Part #2035360-1 1X4 GENERATION Y ASSY KEY A



TE Part #1-1924337-3 Shield Assy, 54 POSN, 0.64mm, 20 DEG BLK



TE Part #9-2208798-5 6POS,0.64 GENER. Y,REC HSG,ASSY



TE Part #917992-6 HYBRID MK-2 PLUG HSG ASSY 26P



#### **Documents**

# **Product Drawings**

**HYBRID MK-2 PLUG HSG ASSY 16P** 

English

#### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_917981-2\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_917981-2\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_917981-2\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages



# MULTILOCK Connector System

English

**Product Specifications** 

**Application Specification** 

English

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

Japanese