

## DEUTSCH | DEUTSCH DT

TE Internal #: DT06-3S-P032

Housing for Female Terminals, Wire-to-Wire, 3 Position, .394 in [10.01 mm] Centerline, Sealable, Gray, Wire & Cable, Power &

Signal, DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DT Series Housings & Connectors



Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [ .063 in ]

Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 10.01 mm [ .394 in ]

All DEUTSCH DT Series Housings & Connectors (461)

## **Features**

## **Product Type Features**

Connector & Housing Shape	Triangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Blank Cavity Position	0
Connector Modification	Enhanced Seal Retention, Shrink Boot Adapter
Number of Positions	3

# **Electrical Characteristics**

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

# **Body Features**

Cable Exit Angle	180°	
Cable Exit / ingle	100	



Body Material	PA GF
Primary Product Color	Gray
Contact Features	
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
	\
Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	10.01 mm[.394 in]
Dimensions	
Product Width	21.29 mm[.838 in]
Product Length	34.75 mm[1.368 in]
Product Height	25.69 mm[1.012 in]
Accepts Wire Insulation Diameter Range	2.23 – 3.68 mm[.088 – .145 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	12mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	1000
Packaging Method	Box



#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts













TE Part # CAT-D487-H342 DEUTSCH DT HEADERS



DEUTSCH DT BACKSHELLS

TE Part # CAT-D48-SFT273 DEUTSCH STAMPED & FORMED

TE Part # CAT-D48-ST273 DEUTSCH SOLID CONTACTS CONTACTS



TE Part # 1011-345-0305 DUST CAP, 3P, PLG, BLK, DT









# Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)



Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

# Customers Also Bought

















TE Part #HD30-24BT-EN-SM BT HD30/HDP20 24 SHL ENH SMALL

## **Documents**

### **Product Drawings**

PLG, 3P, BLK, N, INTEGRATED ADAPTER

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DT06-3S-P032\_99\_c-dt06-3s-p032-99.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT06-3S-P032\_99\_c-dt06-3s-p032-99.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DT06-3S-P032\_99\_c-dt06-3s-p032-99.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Datasheets & Catalog Pages**

**DEUTSCH DT Enhanced Seal Retention Connectors** 

English

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English

**Product Specifications** 

Housing for Female Terminals, Wire-to-Wire, 3 Position, .394 in [10.01 mm] Centerline, Sealable, Gray, Wire & Cable, Power & Signal, DEUTSCH DT



## **Application Specification**

English

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English

Agency Approvals

**UL Report** 

English