DT06-4S-EP06 V ACTIVE

DEUTSCH | DEUTSCH DT

TE Internal #: DT06-4S-EP06

Housing for Female Terminals, Wire-to-Wire, 4 Position, .175 in [4.45 mm] Centerline, Sealable, Black, Wire & Cable, Power &

Signal, DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > DEUTSCH DT Series Housings & Connectors



Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 4.45 mm [.175 in]

All DEUTSCH DT Series Housings & Connectors (461)

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Modification	Enhanced Seal Retention, End Cap
Number of Positions	4
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180°	



Body Material	PA GF
Primary Product Color	Black
Contact Features	
Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Mounting Feature	Without
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.45 mm[.175 in]
Dimensions	
Product Width	20.83 mm[.82 in]
Product Length	32.46 mm[1.278 in]
Product Height	19.58 mm[.771 in]
Row-to-Row Spacing	9.12 mm[.359 in]
Accepts Wire Insulation Diameter Range	2.23 – 3.68 mm[.088 – .145 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Agency/Standard	SAE J2030
Degree of Protection	IP68, IP6K9K
UL Flammability Rating	12mm Flame Test per Standard UL-94



Packaging Features

Serviceable

Packaging Quantity	1000
Packaging Method	Box
Other	

Yes

No

Product Compliance

For compliance documentation, visit the product page on TE.com>

Connector Position Assurance Capable

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-D48-SP729 DEUTSCH SEALING PLUGS



TE Part # DT-RT1

EXT TOOL, FRONT RELEASE

TE Part # CAT-D487-H342 DEUTSCH DT HEADERS



TE Part # CAT-D487-CH8172 DEUTSCH DT Series Housings & Connectors



TE Part # CAT-D48-SFT273 DEUTSCH STAMPED & FORMED CONTACTS



TE Part # CAT-D48-ST273 DEUTSCH SOLID CONTACTS





Also in the Series | DEUTSCH DT



Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(73)



Automotive Housings(619)



Automotive Seals & Cavity Plugs(4)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(14)



PCB Headers & Receptacles(106)

Customers Also Bought







Documents

Product Drawings

PLG, 4P, BLK, N, SEAL RET, CAP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT06-4S-EP06_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT06-4S-EP06_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT06-4S-EP06_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

DEUTSCH DT Enhanced Seal Retention Connectors

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_DT06-4S-EP06_03222018520_dmtec

English

MD_DT06-4S-EP06_03222018520_dmtec

English

Housing for Female Terminals, Wire-to-Wire, 4 Position, .175 in [4.45 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal, DEUTSCH DT



Agency Approvals

UL Report

English