### FASTIN-FASTON | FASTIN-FASTON 375

TE Internal #: 962833-1

Quick Disconnects, Receptacle, 11 - 9 AWG Wire Size, 4 - 6.63 mm<sup>2</sup> Wire Size, Mating Tab Width .375 in [9.53 mm], Straight,


FASTIN-FASTON 375

View on TE.com >




Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: **4 – 6.63 mm²** 

Mating Tab Width: 9.53 mm [.375 in]

Mating Tab Thickness: 1.22 mm [.048 in]

## **Features**

## Product Type Features

Terminates To	Wire & Cable
Wire Stop	No
Wire/Cable Type	Regular Wire
Insertion Force	Normal

#### **Contact Features**

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	9.53 mm[.375 in]
Mating Tab Thickness	1.22 mm[.048 in]
Terminal Orientation	Straight
Contact Base Material	Copper Tin Alloy
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

#### **Mechanical Attachment**

Mating Retention Type	Locking Lance	



Wire Insulation Support	With
Dimensions	
Accepts Wire Insulation Diameter Range	4 – 5.1 mm[.157 – .201 in]
Overall Length	27 mm[1.063 in]
Receptacle Terminal Stock Thickness	.51 mm[.02 in]
Wire Size	4 – 6.63 mm²
Usage Conditions	
Insulation Option	Uninsulated
Packaging Features	
Packaging Quantity	1400
Packaging Method	Reel

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# **Compatible Parts**



TE Part # 2-2150320-2 OC-PA-E-FA-160F220F-001-0124



TE Part # 2150320-2 OC-AT-E-FA-160F220F-001-0124






## Also in the Series | FASTIN-FASTON 375



Crimp Terminal Housings(9)



Insertion & Extraction Tools(1)



Quick Disconnects(20)

# Customers Also Bought



TE Part #1-1718491-2 AMP MCP, UNSEALED CONNECTOR HOUSING



TE Part #936421-2 HYBRID 42P PLUG ASSY BLK



TE Part #1-1718484-4
CARRIER FOR RECEPTACLE INSERTS





## **Documents**

**Product Drawings** 

FF 374 REC 4-6 MM2 0.5X0.27 PLAIN CUSN4

English

**CAD Files** 

Quick Disconnects, Receptacle, 11-9 AWG Wire Size, 4-6.63 mm<sup>2</sup> Wire Size, Mating Tab Width .375 in [9.53 mm], Straight, FASTIN-FASTON 375



**Customer View Model** 

ENG\_CVM\_962833-1\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_962833-1\_E.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_962833-1\_E.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1654742\_HOUSEHOLD\_APPLIANCES\_RAST5

English