



NOTE :
 - MARKING "A" is used to identify "STANDARD" terminal
 - CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm
1	BODY TERMINAL	high conductivity copper alloy thickness=0.2 mm
MARK	DESIGNATION	MATERIAL

PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm ²)	A±0.2	B±0.2	rC ^{+0.15} _{-0.1}	D±0.2	E±0.2	rF±0.1	WEIGHT (g)
0643221029	Sn	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221219	Au 1.27μ MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221039	Sn	Sn	Ni	0.22 to 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221239	Au 1.27μ MINI	Sn	Ni								
0643221019	Sn	Sn	Ni								
0643221229	Au 1.27μ MINI	Sn	Ni								

(SKC) COTES CARACTERISTIQUES SPECIALES
 SPECIAL KEY CHARACTERISTICS
 ■ INDICATION DIMENSIONS S.P.C
 DENOTES S.P.C DIMENSIONS
 ● INDICATION DIMENSIONS CRITIQUES
 DENOTES CRITICAL DIMENSIONS
 ● INDICATION DIMENSIONS FONCTIONNELLES
 DENOTES FUNCTIONAL DIMENSIONS
 QUANTITE PAR FEUILLE INDIVIDUELLE
 QUANTITY PER INDIVIDUAL SHEET
 ■ 1 ● 0 ● 4 (SKC) 0

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: NX RE-MASTERING	
mm	20:1		
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 114689	
ANGULAR TOL	± 2.0°	DRWN: SSUVARNA	2017/07/05
4 PLACES	± 0.1	CHK'D: SLAFAURE	2018/06/04
3 PLACES	± 0.1	APPR: SLAFAURE	2018/06/14
2 PLACES	± 0.1	INITIAL REVISION:	
1 PLACE	± 0.1	DRWN: FPAROLARI	2007/09/17
0 PLACES	± 0.1	APPR: LSTICKEIR	2007/09/17
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	FIRST ANGLE PROJECTION	DRAWING	SERIES
		A1-SIZE	64322
DOCUMENT STATUS		MATERIAL NUMBER	CUSTOMER
P1	RELEASE DATE	SEE CHART	GENERAL MARKET
2018/06/14	12:23:38	SD-64322-001	
DOCUMENT NUMBER		DOC TYPE	DOC PART
PSD		000	E1
SHEET NUMBER		1 OF 1	