


Home: Crimp Housings >

Part Number: 03-06-1152
1.57mm Diameter Standard .062" Pin and Socket Receptacle Housing, 15 Circuits, without Mounting Ears



Series image - Reference only

Table with 2 columns: Label (Status, Series, Category, Overview, Engineering/Old PN) and Value (Planned for Obsolescence, 1625, Crimp Housings, Standard .062" Pin and Socket Power Connectors, 1625-15R1)

CHECK DISTRIBUTOR INVENTORY

- Add to My Parts
Email this page

Go to Part Detail

Mates With Part(s):
03-06-2151, 03-06-2152, 03-06-7152, 03-06-7155

Use With:
Female Crimp Terminals 1561, 4559, 4529, 2190, 2189, 1787, 1855
Male Crimp Terminals 1560, 1786, 1854
1778 Male PC Tail Terminals
1779 Female PC Tail Terminals

Application Tooling FAQ

Tooling specifications and manuals are found by selecting the products below.
Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling
Check our list of old tooling that used to be available for this part

Specifications & Other Documents:

Note - Please disable browser pop-up blockers to view documents on www.molex.com

Product Environmental Compliance

Questions on Product Environmental Compliance? Email productcompliance@molex.com

EU ELV: Not Relevant
EU RoHS: Compliant
China RoHS:
REACH SVHC: Not Contained Per - ED/79/2015 (17 December 2015)
Low-Halogen Status: Low-Halogen

- RoHS Certificate of Compliance (PDF)
Multiple Part Product Compliance Form

Part Detail COLLAPSE ALL

General

Table with 2 columns: Field (Status, Category, Series, Application, Comments, Overview, Product Name, UPC) and Value (Planned for Obsolescence, Crimp Housings, 1625, Power, Wire-to-Wire, Polarized to Mating Part, Standard .062" Pin and Socket Power Connectors, Standard .062", 800753615168)

Physical

Table with 2 columns: Field (Breakaway, Circuits (maximum), Circuits Detail, Color - Resin, Flammability) and Value (No, 15, 3x5, Natural, 94V-2)

Gender	Receptacle
Glow-Wire Compliant	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	3.202/g
Number of Rows	3
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	3.68mm
Pitch - Termination Interface	3.68mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +105°C

▼

Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	5.0A
-------------------------------	------

▼

Agency Certification

Please find UL Certificates by searching the UL Database using the Molex Series Number. [Click here to visit the UL Database](#)

CSA	LR19980
UL	E29179

▼

Solder Process Data

Lead-freeProcess Capability	N/A
-----------------------------	-----

▼

Material Info

Old Part Number	1625-15R1
-----------------	-----------

▼

Reference - Drawing Numbers

Packaging Specification	PK-1625-003
Product Specification	PS-02-06
Sales Drawing	SD-1625-15*

PRODUCTS

- Antennas
- Application Tooling
- Cable Assemblies
- Connectors
- Copper Flex
- Electrical Products
- Industrial Automation
- Membrane Switches
- Optical Solutions
- PCB Assemblies
- Solid State Lighting

QUICK LINKS

- Contact Molex
- Cross-Reference
- Industries
- Literature
- Press Room / Press Releases
- Product Index
- Sitemap

RESOURCES

- California Supply Chains Act
- Careers
- Compliance
- ecocare
- Feedback | Help
- Legal | Trademarks
- Mobile Site
- Supplier Portal
- Privacy Policy

STAY CONNECTED



