## AMP | AMPSEAL

TE Internal #: 1-776163-5

PCB Mount Header, Right Angle, Wire-to-Board, 35 Position, .157 in [4 mm] Centerline, Fully Shrouded, Gold over Nickel, Through

Hole - Solder, AMPSEAL

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > AMPSEAL PCB Horizontal Headers



Connector System: Wire-to-Board

Number of Positions: 35

Centerline (Pitch): 4 mm [.157 in]

Sealable: Yes

PCB Mount Orientation: Right Angle

All AMPSEAL PCB Horizontal Headers (54)

## **Features**

### **Product Type Features**

Primary Product Color

Connector Code

**Contact Features** 

Contact Size

Contact Type

| 1 Toduct Type Teatures            |                       |
|-----------------------------------|-----------------------|
| Connector & Housing Shape         | Rectangular           |
| PCB Connector Assembly Type       | PCB Mount Header      |
| Header Type                       | Fully Shrouded        |
| Connector System                  | Wire-to-Board         |
| Sealable                          | Yes                   |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features            |                       |
| Number of Positions               | 35                    |
| PCB Mount Orientation             | Right Angle           |
| Number of Rows                    | 3                     |
| Body Features                     |                       |
|                                   |                       |

Blue

10, 22, 5

1.3mm

Pin



| Contact Mating Area Plating Material        | Gold over Nickel           |
|---|----------------------------|
| Contact Current Rating (Max)                | 11 A                       |
| Termination Features                        |                            |
|   | Through Holo Coldon        |
| Termination Method to Printed Circuit Board | Through Hole - Solder      |
| Mechanical Attachment                       |                            |
| Mating Alignment Type                       | Keyed                      |
| Mating Alignment                            | With                       |
| PCB Mount Alignment                         | With                       |
| PCB Mount Retention                         | With                       |
| Connector Mounting Type                     | Board Mount                |
| Housing Features                            |                            |
| Centerline (Pitch)                          | 4 mm[.157 in]              |
| Usage Conditions                            |                            |
| Operating Temperature Range                 | -40 – 105 °C[-40 – 221 °F] |
| Operation/Application                       |                            |
| Circuit Application                         | Power & Signal             |
| Industry Standards                          |                            |
| Degree of Protection                        | IP6K7, IP6K9K              |
| UL Flammability Rating                      | UL 94V-0                   |
| Packaging Features                          |                            |
| Packaging Type                              | Tray                       |
| Packaging Quantity                          | 160                        |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2022<br>(223)<br>Candidate List Declared Against: JAN 2022<br>(223)<br>Does not contain REACH SVHC |



| Halogen Content | Not Low Halogen - contains Br or Cl > 900 |
|-----------------|---|
|                 | ppm.                                      |

## Solder Process Capability

Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**



## Also in the Series | AMPSEAL



Automotive Connector Caps & Covers (7)



Automotive Connector Locks & Position Assurance(1)



Automotive Housings(31)



Automotive Seals & Cavity Plugs(1)



Automotive Terminals(8)



PCB Headers & Receptacles(109)



# Customers Also Bought







TE Part #640456-7 07P MTA100 HDR ASSY F/L SQ STR





TE Part #1825967-1
FSMCDH=6.0mm Tact W/SQ Act. & High Temp



TE Part #2-1571552-2 808-AG11D-ESL-LF=800 DIP,GF/SN

TE Part #1977264-2
FSM4LPASTR=TACT SWITCH,SMT,
T&R

TE Part #1-1571983-5
GDH02STRON04=DIP SWITCH

## **Documents**

## **Product Drawings**

35POS,AMPSEAL,PIN HSG ASSY,SLD,COD 5

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-776163-5\_S.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-776163-5\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-776163-5\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**AMPSEAL Connector Catalog** 

English

ICT Terminals and Connectors Catalogue

English

## **Product Specifications**

**Application Specification** 

PCB Mount Header, Right Angle, Wire-to-Board, 35 Position, .157 in [4 mm] Centerline, Fully Shrouded, Gold over Nickel, Through Hole - Solder, AMPSEAL



English

Agency Approvals

**UL Report** 

English