




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **1**

Sealable: **No**

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	1
PCB Mount Orientation	Vertical
Number of Power Positions	1
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------



Body Features

Connector Profile	Low
-------------------	-----

Contact Features

Contact Layout	Inline
Contact Base Material	Brass
Contact Current Rating (Max)	8 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	1 μm[39.37 μin]
Contact Termination Area Plating Thickness	.8 μm[31.49 – 70.86 μin]

Termination Features

Termination Post & Tail Length	3.7 mm[.146 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Mating Retention	With
Mating Retention Type	Latch

Housing Features

Housing Color	Natural
Housing Material	Nylon 66

Dimensions

PCB Thickness (Recommended)	.06 mm[1.6 in]
Width	10.7 mm[.421 in]
Height	13.4 mm[.52 in]
Length	8.8 mm[.34 in]

Usage Conditions

Operating Temperature Range	-25 – 105 °C[-13 – 221 °F]
-----------------------------	----------------------------



Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Method	Bag
Packaging Quantity	1000

Other

For Use With	Plug Housing
--------------	--------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 1-1123823-1
EP IP PLUG NATURAL

Also in the Series

Economy Power

Connector Contacts(1)

Insertion & Extraction Tools(1)

PCB Headers & Receptacles(166)

PCB Latches, Locks & Retainers(2)

Power Contacts(8)

Rectangular Connector Housings(1)




Rectangular Power Connectors(285)

Wire-to-Board Connector Assemblies & Housings(64)

Wire-to-Board Connector Contacts(6)

Customers Also Bought



 TE Part #179849-1 STD Temp Power Double Lock Header	 TE Part #3-1971906-4 HEADER ASSY 8POS,KEYING-C,NEW GIC3.3	 TE Part #917730-1 2.5 SIGNAL D/LOCK HDR ASSY 10P	 TE Part #5-1376387-1 5.0 POWER KEY CONNECTOR 6P (2R
 TE Part #5-1376386-1 5.0 POWER KEY CONNECTOR 4P (2R	 TE Part #1903388-1 GIC 2.5 W PLUG HSG 2P NATURAL	 TE Part #4-1123824-1 EP 1P HDR RED	 TE Part #5-917698-1 2.5 SIGNAL DBL LOCK D.L.P 2P
 TE Part #3-1376386-5 5mm B-T-W Conn. 4P(2row) HDR A			

Documents

Product Drawings
EP 1P HDR NATURAL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1123824-1_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1123824-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1123824-1_D.3d_stp.zip

English

3D PDF

English



Customer View Model

[ENG_CVM_1-1123824-1_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_1-1123824-1_B.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_1-1123824-1_B.2d_dxf.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[MD_1-1123824-1_06082018844_dmtec](#)

English

[MD_1-1123824-1_06082018844_dmtec](#)

English

Instruction Sheets

[Instruction Sheet \(non U.S.\)](#)

Japanese

[Economy Power \(EP\) Connector](#)

Japanese

Agency Approvals

[UL Report](#)

English