# 106351-1 ✓ ACTIVE

#### **EUROCARD**

TE Internal #: 106351-1

Eurocard Connectors, Plug, Board-to-Board, 48 Position, .078 in [2 mm] Centerline, Printed Circuit Board, 3 Row, Right Angle, 16 Column

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > Eurocard Connectors



Connector & Housing Type: Plug
Connector System: Board-to-Board

Termination Post & Tail Length: 2.9 mm [.114 in]

Number of Positions: 48

Centerline (Pitch): 2 mm [.078 in]

#### **Features**

#### **Product Type Features**

## **Configuration Features**

Number of Positions	48
Number of Rows	3
PCB Mount Orientation	Right Angle
Number of Columns	16
Number of Signal Positions	48
Rows Loaded	Z, B, D



Pin
.76 μm
Gold
Tin-Lead
Brass
5.5 A
Through Hole - Solder
2.9 mm[.114 in]
Polarization
Without
With

Mating Alignment	With
PCB Mount Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	With

PCB Mount Retention Type Mounting Hole Connector Mounting Type **Board Mount** 

# **Housing Features**

Housing Material	Thermoplastic Polyester - GF
Housing Color	Gray
Centerline (Pitch)	2 mm[.078 in]

## **Dimensions**

Connector Height	21.8 mm
Row-to-Row Spacing	3.81 mm[.15 in]

# **Usage Conditions**

Operating Temperature Range -55 – 125 °C[-67 – 257 °F]	
--	--

## Operation/Application

# Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------



#### **Packaging Features**

Packaging Method	Tray	
------------------	------	--

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




# Customers Also Bought





TE Part #1367073-1 20 POS SMT CONN, SFP, 15AU



TE Part #292161-2 CT P/HDR ASSY V 2P W/KINK NAT













TE Part #1-1571995-2 510-AG92D-12LF= SIP RoHS, TIN/TIN

#### **Documents**

Product Drawings
48P.IEC-F MALE CONN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_106351-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_106351-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_106351-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

Eurocard Connectors, Plug, Board-to-Board, 48 Position, .078 in [2 mm] Centerline, Printed Circuit Board, 3 Row, Right Angle, 16 Column



Workmanship Specification

English