Our commitment. Your advantage.

Search

Products

Documentation

Resources

My Account

Customer Support

Home > Products > By Type > Ribbon and Flat Flex Wire Connectors - Ribbon Cable > Product Feature Selector > Product Details


111623-7 Product Details



Live Product Chat

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product



Ribbon Cable Connectors (AMP-LATCH)

Product Highlights:

- Connector Type = .079 [2.0mm] AMP-LATCH
- Number of Positions = 30
- Receptacle
- Mating Polarization Type = Center
- With Mating Polarization

111623-7 <u>View all Features</u>

TE Internal Number: 111623-7

Superseded

Search for Replacement Parts





Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)





Documentation & Additional Information

Product Drawings:

• RECEPTACLE ASSY, POLARIZED, 2mm CL, AMP-LATCH (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

• CONNECTOR, AMP-LATCH, 2 MM, RIBBONCABLE RECEPTACLE (PDF, English)

Application Specifications:

AMP-LATCH 2 mm Receptacle Connectors (PDF, English)

Instruction Sheets:

• Connector-Specific Kit f/AMP-LATCH 2mm Receptacle Co... (PDF, English)

CAD Files:

• None Available

Additional Information:

Product Line Information

Related Products:

• <u>Tooling</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Connector Type = .079 [2.0mm] AMP-LATCH
- Number of Positions = 30
- Gender = Receptacle
- Mating Polarization Type = Center
- <u>Mating Polarization</u> = With
- <u>Mounting Ears</u> = Without
- PCB Retention Feature = No
- Mating Connector Lock = Without
- Strain Relief = Without
- With Cover Preassembled = Yes
- Cover Type = Feed Thru
- Comment = Accepts 28 AWG [0.08-0.09mm²] ribbon cable, 0.61-0.97 [.024-.038] thick PVC 1.00 [.039] pitch.

Termination Related Features:

• <u>Solder Tail Contact Plating</u> = Tin-Lead

Body Related Features:

• Centerline, Matrix (mm [in]) = 2.00 x 2.00 [.079 x .079]

Contact Related Features:

List all Documents

- Contact Mating Area Plating Material = Gold (30)
- Contact Base Material = Beryllium Copper

Housing Related Features:

- Housing Color = Black
- Housing Material = Polyester
- Housing Flammability Rating = UL 94V-0

Configuration Related Features:

• Cable Stop = Without

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

Conditions for Usage:

• <u>Terminate To</u> = Ribbon Cable

Other:

Brand = AMP