



NOTES / Bemerkungen:

1) MATERIAL: PA66-GF25 black, Ultramid A3X2G5 BK
Material: PA66-GF25 schwarz, Ultramid A3X2G5 BK

2) FLAMMABILITY: UL94: V0
Brennbarkeit: UL94: V0

3) IP67 RATED ACHIEVED WHEN PROTECTION CAP IS MATED WITH M12 CONNECTOR (ACCORDING IEC 61076-2-101) AND FIXED WITH LOCKED TORQUE: 0,5 Nm.
Schutzart IP67 wird erreicht wenn die Schutzkappe mit einem M12 Steckverbinder, nach IEC 61076-2-101, montiert und mit einem Drehmoment: 0,5 Nm, angezogen wird.

4) TEMPERATURE RANGE: -40°C +115°C
Temperatur Bereich: -40°C +115°C

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
QUALITY SYMBOLS	2016/01/25 2016/02/05 2016/02/05	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION UNITS	SCALE						
		ANGULAR TOL ± 1.0 °		mm	5:1						
▽A = 0	EC NO: 102635 DRWN: JELIZAINCIN CHK'D: RSILLER APPR: RSILLER	4 PLACES ±	DATE	JELIZAINCIN	2016/01/25	ACC PCAP M12 FE OR 9X1					
▽E = 0		3 PLACES ±		CHK'D BY	DATE						
▽B = 0		2 PLACES ± 0.05	DATE	RSILLER	2016/02/05	PRODUCT CUSTOMER DRAWING					
▼ = 0		1 PLACE ± 0.1									
▽C = 0		0 PLACES ± 0.2	DRAWING SIZE	THIRD ANGLE PROJECTION	SERIES	MATERIAL NUMBER	CUSTOMER				
⊗ = 0		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	A3		120358	1203580007					
■ = 0			DOCUMENT NUMBER	DOC TYPE	DOC PART	SHEET NUMBER					
▽ = 0	A	REV		1203580007	PSD	010	1 OF 1				