

# 111626-6 Product Details



**111626-6**

TE Internal Number: 111626-6



**Superseded**

[Search for Replacement Parts](#)

## Ribbon Cable Connectors (AMP-LATCH)

[Not EU RoHS or ELV Compliant](#) ([Find RoHS Compliant Alternates](#))

### Product Highlights:

- Connector Type = .079 [2.0mm] AMP-LATCH
- Number of Positions = 26
- Receptacle
- Without Mating Polarization
- Terminate To Ribbon Cable

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RECEPTACLE ASSY, 2mm CL, AMP-LATCH</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">CONNECTOR, AMP-LATCH, 2 MM, RIBBONCABLE RECEPTACLE</a> (PDF, English)</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">AMP-LATCH 2 mm Receptacle Connectors</a> (PDF, English)</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Connector-Specific Kit f/AMP-LATCH 2mm Receptacle Co...</a> (PDF, English)</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>
--	--

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Connector Type = .079 [2.0mm] AMP-LATCH</li> <li>• <a href="#">Number of Positions</a> = 26</li> <li>• Gender = Receptacle</li> <li>• <a href="#">Mating Polarization</a> = Without</li> <li>• <a href="#">Mounting Ears</a> = Without</li> <li>• PCB Retention Feature = No</li> <li>• Mating Connector Lock = Without</li> <li>• Strain Relief = Without</li> <li>• With Cover Preassembled = Yes</li> <li>• Cover Type = Feed Thru</li> <li>• Comment = Accepts 28 AWG [0.08-0.09mm<sup>2</sup>] ribbon cable, 0.61-0.97 [.024-.038] thick PVC 1.00 [.039] pitch.</li> </ul> <p><b>Termination Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Solder Tail Contact Plating</a> = Tin-Lead</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• Centerline, Matrix (mm [in]) = 2.00 x 2.00 [.079 x .079]</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Contact Mating Area Plating Material</a> = Gold (30)</li> <li>• Contact Base Material = Beryllium Copper</li> </ul>	<p><b>Housing Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Housing Color</a> = Black</li> <li>• Housing Material = Polyester</li> <li>• Housing Flammability Rating = UL 94V-0</li> </ul> <p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• Cable Stop = Without</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not relevant for lead free process</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Terminate To</a> = Ribbon Cable</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = AMP</li> </ul>
---	---