111196-7 - ACTIVE

AMP-LATCH

TE Internal #: 111196-7 Ribbon Cable Connectors, Cable-to-Board, 30 Position, .05 in [1.27 mm] Centerline, Insulation Displacement (IDC), 2 Row, Receptacle View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors



Connector System: Cable-to-Board Number of Positions: 30 Centerline (Pitch): 1.27 mm [.05 in] Termination Method to Wire & Cable: Insulation Displacement (IDC)

Row-to-Row Spacing: 2.54 mm [.1 in]

Features

Product Type Features

Connector Type	Connector Assembly
Connector Product Type	Connector Assembly
Connector System	Cable-to-Board
Connector & Housing Type	Receptacle

Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Compatible With Wire & Cable Type	Ribbon Cable
Number of Positions	30
Number of Rows	2
Electrical Characteristics	
Insulation Resistance	5000 MΩ
Operating Voltage	30 VAC
Body Features	
Mating Retention Feature Material	Stainless Steel
Contact Features	
Contact Layout	Matrix
Mating Square Post Dimension	.38 mm[.015 in]

Ribbon Cable Connectors, Cable-to-Board, 30 Position, .05 in [1.27 mm] Centerline, Insulation Displacement (IDC), 2 Row, Receptacle



Mating Pin Diameter	.38 mm[.015 in]	
Wire Contact Termination Area Plating Thickness	2.54 – 5.08 μm[100 – 200 μin]	
Wire Contact Termination Area Plating Material	Tin-Lead	
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]	
Contact Mating Area Plating Material	Gold	
Contact Underplating Material	Nickel	
Contact Base Material	Copper Alloy	
Contact Current Rating (Max)	.5 A	
Termination Features		
Square Termination Post & Tail Dimension	.38 mm[.015 in]	
Round Termination Post & Tail Diameter	.38 mm[.015 in]	
Termination Method to Wire & Cable	Insulation Displacement (IDC)	
Mechanical Attachment		
Mating Alignment	With	
Panel Mount Feature	Without	
Mating Alignment Type	Polarization	
Mating Retention	With	
Mating Retention Type	Latch	
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Housing Material	Thermoplastic	
Housing Color	Black	
Centerline (Pitch)	1.27 mm[.05 in]	
Dimensions		
Connector Length	25.4 mm[1 in]	
Connector Height	12.32 mm[.485 in]	
Connector Width	6.45 mm[.254 in]	
Row-to-Row Spacing	2.54 mm[.1 in]	
Usage Conditions		
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]	
Operation/Application		
Circuit Application	Signal	

C For support call+1 800 522 6752

Ribbon Cable Connectors, Cable-to-Board, 30 Position, .05 in [1.27 mm] Centerline, Insulation Displacement (IDC), 2 Row, Receptacle



Industry Standards

CSA File Number	LR 7189	
UL Rating	Recognized	
Agency/Standard	CSA, UL	
UL File Number	E28476	
UL Flammability Rating	UL 94V-0	
Packaging Features		
Packaging Quantity	50	
Packaging Method	Tray	
Product Compliance For compliance documentation, visit the product page on TE.com>		
Product Compliance	Not Compliant	
Product Compliance For compliance documentation, visit the product page on TE.com>		
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Not Compliant	

Halogen Content

Solder Process Capability

SVHC > Threshold:

Pb (13% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Low Halogen - contains Br or Cl > 900 ppm.

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

& For support call+1 800 522 6752

Ribbon Cable Connectors, Cable-to-Board, 30 Position, .05 in [1.27 mm] Centerline, Insulation Displacement (IDC), 2 Row, Receptacle





Customers Also Bought



DTB 26 B 11-01 AN	DTB 26 B 13-35 BN	HFW1130G01 = M39016/6-111L	214A321-3-02/42-0
		E	
TE Part #147681-000 214A342-3-02/42-0	TE Part #821895-000 214A352-3-02/42-0	TE Part #ZPF00000000015826 DTB 26 B 19-35 AN	TE Part #ZPF000000000015835 DTBC 20-09

DTBC 24-11

TE Part #ZPF00000000015839

TE Part #724113-000

KTKK-1123

Documents

Ribbon Cable Connectors, Cable-to-Board, 30 Position, .05 in [1.27 mm] Centerline, Insulation Displacement (IDC), 2 Row, Receptacle



Product Drawings 030 RCPT SYSTEM 50 30 DPLX

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_111196-7_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_111196-7_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_111196-7_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance TE Material Declaration

English

Agency Approvals Agency Approval Document

English