
# 147377-9 - ACTIVE

## AMPMODU | AMPMODU System 50

TE Internal #: 147377-9 PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 24 Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold, AMPMODU System 50

View on TE.com >





PCB Connector Assembly Type: PCB Mount Header

PCB Mount Orientation: Vertical

Connector System: Board-to-Board, Wire-to-Board

Number of Positions: 24

Number of Rows: 2

## Features

## Product Type Features

PCB Connector Assembly Type

Connector System

Header Type

PCB Mount Header

Board-to-Board, Wire-to-Board

Fully Shrouded



Sealable	No	
Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Connector Contact Load Condition	Fully Loaded	
PCB Mount Orientation	Vertical	
Number of Positions	24	
Number of Rows	2	
Electrical Characteristics		
Dielectric Withstanding Voltage (Max)	500 V	
Operating Voltage	30 VAC	
Body Features		
Primary Product Color	Black	
Contact Features		
	150 µin	
Contact Shape & Form	Round	

PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 24 Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold, AMPMODU System 50



Contact Mating Area Plating Material Finish	Bright	
PCB Contact Termination Area Plating Material	Tin	
Contact Base Material	Phosphor Bronze	
Contact Mating Area Plating Material	Gold	
Contact Type	Pin	
Contact Current Rating (Max)	1 A	
Termination Features		
	.031 in	
Termination Method to Printed Circuit Board	Surface Mount	
Mechanical Attachment		
Mating Retention	With	
Panel Mount Feature	With	
Mating Alignment	With	
Mating Alignment Type	Latched	
PCB Mount Retention	Without	
PCB Mount Retention PCB Mount Alignment	Without	

#### Housing Features

Centerline (Pitch)	1.27 mm[.05 in]	
Housing Material	PPA	
Dimensions		
	.1 in	
Usage Conditions		
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]	
Operation/Application		
Solder Process Feature	Board Standoff	
Circuit Application	Power & Signal	
Industry Standards		
Approved Standards	CSA LR7189, UL E28476	
UL Flammability Rating	UL 94V-0	
Packaging Features		
Packaging Quantity	250	

**C** For support call+1 800 522 6752

PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 24 Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold, AMPMODU System 50



Packaging Type

Tape & Reel

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Not Compliant

Not Compliant

Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2022 (224)

Candidate List Declared Against: JAN 2022

(223)

SVHC > Threshold:

Pb (13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Reflow solder capable to 260°C

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**




PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 24 Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold, AMPMODU System 50





# Also in the Series | AMPMODU System 50



PCB Headers & Receptacles(1014)

# Customers Also Bought



	E TE		
TE Part #5646547-1 Z-PACK A-B 25 COLUMN SHLD ASSY	TE Part #YD369-HP99-NP00000 369 HARSH 9 WAY PLUG, PIN - BACC65CP3PN	TE Part #1053398-1 2064 8002 90	TE Part #320572 PIDG R 22-16COMM 22-18MIL 5/16



## Documents

## Product Drawings 24 SYS50 SMT HDR DR SHD W/O HD

English

#### **CAD** Files

3D PDF

3D

PCB Mount Header, Vertical, Board-to-Board / Wire-to-Board, 24 Position, .05 in [1.27 mm] Centerline, Fully Shrouded, Gold, AMPMODU System 50



**Customer View Model** 

ENG\_CVM\_CVM\_147377-9\_J.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_147377-9\_J.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_147377-9\_J.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Product Environmental Compliance TE Material Declaration

English