

TE Internal #: 1473244-3

Housing for Female Terminals, Wire-to-Board, 81 Position, .228 in / .

1 in [5.8 mm / 2.54 mm] Centerline, Sealable, Black, Wire & Cable,

Signal

View on TE.com >



Connectors > Automotive Connectors > Connector Housings











Connector & Housing Type: Housing for Female Terminals

Connector System: Wire-to-Board

Number of Positions: 81

Centerline (Pitch): 2.54 mm, 5.8 mm [.1 in, .228 in]

Sealable: Yes

Features

Product Type Features

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Board
Sealable	Yes
Hybrid Connector	Yes
Primary Locking Feature	Integrated in Housing
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	81
Number of Rows	3, 4
Electrical Characteristics	
Nominal Voltage Architecture	12 V
Body Features	
Body Material	PBT



Primary Product Color	Black
Contact Features	
Contact Size	.63mm, 2.8mm
Mechanical Attachment	
Mating Alignment Type	Polarizing Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	2.54 mm, 5.8 mm[.1 in][.228 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operation/Application	
Circuit Application	Signal
Other	

Product Compliance

For compliance documentation, visit the product page on TE.com>

Connector Position Assurance Capable

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

No



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







121pos hybrid MQS .63 header 90deg











TE Part # 1473246-1 SEALED MQS CLAENBODY/JPT 81POS TE Part # 368377-2 FRONT BODY REC HSG FOR 81P(B)

TE Part # 368904-1 76 WAY FAMILY SEAL 81P REC HSG TE Part # 368905-1
PERIPHERAL SEAL 81P REC HSG

TE Part # 368380-1
SEAL RETAINER FOR 81P BLACK



Customers Also Bought






















Documents

Product Drawings

MQS/JPT 81POS PLUG ASSY

Japanese

MQS/JPT 81POS PLUG ASSY

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_1473244-3_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1473244-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1473244-3_A.3d_stp.zip

Housing for Female Terminals, Wire-to-Board, 81 Position, .228 in / .1 in [5.8 mm / 2.54 mm] Centerline, Sealable, Black, Wire & Cable, Signal



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English