

FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 160928-3

Quick Disconnects, Receptacle, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Straight,

FASTIN-FASTON 250

View on TE.com >



Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: .51 – 1.03 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

Terminates To	Wire & Cable
Wire Stop	No
Wire/Cable Type	Regular Wire
Insertion Force	Normal
Sealable	No

Configuration Features

Connection Capacity Single	
----------------------------	--

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Unplated
Crimp Type	F-Crimp



Barrel Type	Open
Mechanical Attachment	
Mating Retention Type	Locking Lance
Wire Insulation Support	With
Dimensions	
Accepts Wire Insulation Diameter Range	1.4 – 2.3 mm[.055 – .09 in]
Overall Length	19.2 mm[.755 in]
Receptacle Terminal Stock Thickness	.33 mm[.013 in]
Wire Size	.51 – 1.03 mm²
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Packaging Features	
Packaging Quantity	5000
Packaging Method	Strip/Reel
Other	
Comment	Chamfered, Without Dimple

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











TE Part # 2-2150155-2 OCEAN_2.0_Applicator-E-080F110OV



TE Part # 2150155-1 OCEAN_2.0_Applicator-E-080F110OV



TE Part # 2150155-2 OCEAN_2.0_Applicator-E-080F110OV




TE Part # 626094-1 TERMINAL, .250 FASTIN-ON REC



TE Part # 7-2150155-1 OCEAN_2.0_Applicator-E-080F110OV



TE Part # 7-2150155-2 OCEAN_2.0_Applicator-E-080F110OV



Also in the Series | FASTIN-FASTON 250










Insertion & Extraction Tools(2)



PCB Terminals(2)




Customers Also Bought













Documents

Product Drawings

FF 250 REC 0.5-1.0MM2 PH.PB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160928-3_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160928-3_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160928-3_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Quick Disconnects, Receptacle, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Straight, FASTIN-FASTON 250



Product Environmental Compliance

Product Compliance

English

Product Compliance

English