## **Aptiv** Connection Systems Catalog



Find by Feature	Browse by Category	Browse by Appl
15326265 Enter part number	r or keyword	Search
Search Result	s (1) Search Option	s
1 Result(s): [ A	M/] - 15326265	
	- GT 150 Series Female 9 rminal, Cable Range 0.75	
Compare		
	<u>«</u>	<u> </u>

## GT 150 Series Female Sealed Tin Plating Terminal, Cable Range 0.75 - 1.00 mm2

Part # 15326265

Question about this product?

Attributes Part #: 15326265  ${\it GT\,150\,Series\,Female\,Sealed\,Tin\,Plating\,Terminal,\,Cable\,Range}$ Description: Product Type : Terminal Active Status: Terminal Family: 150 Series: Gender: Female Sealable: Sealed Material: CuSn3Zn9 0 Weight [g]: Plating: Minimum Cable Diameter [mm]: 1.70 Maximum Cable Diameter [mm]: 2 25 **Minimum Cable Core Cross Section** 0.75 [mm2]: **Maximum Cable Core Cross Section** 1.00 [mm2]: -40 to 125 Temperature Range: **Voltage Drop:** Less than 10.0

doesn't function properly

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.

Remarks:

· APTIV •



special cavity required to use this terminal (cavity with nose guard). use only when mating with blunt male blade. p/n 12191819

Contact Us Suppliers E-Catalog Legal

© 2017 Aptiv. All rights reserved