

Modular Hard Wired Fuse and Relay Box

TE Internal #: 1534968-2 Hard Wired Box Accessories, Screw, None, -40 – 105 °C [-40 – 221 ° F], Modular Hard Wired Fuse and Relay Box

View on TE.com >

Connectors > Automotive Connectors > Power Distribution Boxes > Hard Wired Box Accessories



Hardware Accessory Type: Screw

UL Flammability Rating: None

Sealable: No

Operating Temperature Range: -40 – 105 °C [-40 – 221 °F]

Features

Product Type Features

Hardware Accessory Type	Screw
Sealable	No
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]



Industry Standards

UL Flammability	Rating
-----------------	--------

None

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Not Yet Reviewed	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not reviewed for solder process capability	

Product Compliance Disclaimer

1534968-2

Hard Wired Box Accessories, Screw, None, -40 – 105 °C [-40 – 221 °F], Modular Hard Wired Fuse and Relay Box



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | Modular Hard Wired Fuse and Relay Box


	Minute Income	And the second	
Automotive Housings(1)	Battery Distribution Units(6)	Busbars & Terminals(5)	Hard Wired Box Accessories(11)
Hard Wired Boxes with Busbars(3)	Insertion & Extraction Tools(3)	Module Components(9)	Other Hard Wired Boxes(6)

Customers Also Bought

1534968-2

Hard Wired Box Accessories, Screw, None, -40 – 105 °C [-40 – 221 °F], Modular Hard Wired Fuse and Relay Box







TE Part #928930-1 FF 110 TAB 0.5-1 MM2 .080 F SSP CUZN30



TE Part #2141033-1 COVER,FOR PRE FUSE MODULE

Documents

Product Drawings BOLT M5 WITH SQUARE HEAD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1534968-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1534968-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1534968-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

C For support call+1 800 522 6752

1534968-2

Hard Wired Box Accessories, Screw, None, -40 – 105 °C [-40 – 221 °F], Modular Hard Wired Fuse and Relay Box



MFINITY Modular Hard Wired Fuse and Relay Box

English