

TE Internal #: 1612901-1

DC Jack Connectors, Board-to-Board, 3 Position, 2 mm [.079 in]

Centerline, Receptacle, 30 VDC, Right Angle, Printed Circuit Board,

Signal, Board Mount

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Board-to-Board

Number of Positions: 3

Centerline (Pitch): 2 mm [.079 in]

Connector & Housing Type: Receptacle

Operating Voltage: 30 VDC

Features

Product Type Features

Troduct Type reatures	
Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	3
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	30 VDC
Contact Features	
Contact Current Rating (Max)	2 A
Mechanical Attachment	
PCB Mount Retention	With
PCB Mount Retention Type	Locating Post



Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	2 mm[.079 in]
Usage Conditions	
Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]
Operation/Application	
Circuit Application	Signal

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Customers Also Bought















Documents

Product Drawings

BATTERY BLOCK CONN. REC ASSY 3

English

CAD Files

Customer View Model

ENG_CVM_CVM_1612901-1_B.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1612901-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1612901-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

DC Jack Connectors, Board-to-Board, 3 Position, 2 mm [.079 in] Centerline, Receptacle, 30 VDC, Right Angle, Printed Circuit Board, Signal, Board Mount



Datasheets & Catalog Pages

Products for Mobile Equipment

English

POWER_CONNECTORS_CATALOG_SEC09_LAPTOPS_PORTABLES

English

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English