

160915-2 ✓ ACTIVE

FASTON | FASTON 250

TE Internal #: 160915-2

Quick Disconnects, Receptacle, 20 – 17 AWG Wire Size, .5 – 1 mm² Wire Size, Mating Tab Width .25 in [6.35 mm], Straight, Phosphor Bronze, FASTON 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .5 – 1 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

| | |
|-----------------|--------------|
| Terminates To | Wire & Cable |
| Wire/Cable Type | Regular Wire |
| Wire Stop | No |
| Insertion Force | Low |
| Sealable | No |

Configuration Features

| | |
|---------------------|--------|
| Connection Capacity | Single |
|---------------------|--------|

Contact Features

| | |
|--------------------------------|------------------|
| Quick Disconnect Terminal Type | Receptacle |
| Mating Tab Width | 6.35 mm [.25 in] |
| Mating Tab Thickness | .81 mm [.032 in] |
| Terminal Orientation | Straight |
| Contact Base Material | Phosphor Bronze |
| Terminal Plating Material | Tin |
| Crimp Type | F-Crimp |



| | |
|-------------|------|
| Barrel Type | Open |
|-------------|------|

Mechanical Attachment

| | |
|-------------------------|-----------|
| Mating Retention Type | Dimple |
| Extraction Force | 80 Newton |
| Wire Insulation Support | With |

Dimensions

| | |
|--|--------------------------------|
| Accepts Wire Insulation Diameter Range | 1.4 – 2.31 mm [.055 – .091 in] |
| Overall Length | 19 mm [.748 in] |
| Receptacle Terminal Stock Thickness | .41 mm [.016 in] |
| Wire Size | .5 – 1 mm ² |

Usage Conditions

| | |
|-----------------------------|-----------------------------|
| Insulation Option | Uninsulated |
| Operating Temperature Range | -40 – 110 °C [-40 – 230 °F] |

Packaging Features

| | |
|--------------------|------------|
| Packaging Quantity | 5000 |
| Packaging Method | Strip/Reel |

Other

| | |
|------|---------|
| Line | Premier |
|------|---------|

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

| | |
|---|--|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-2150158-1
 OCEAN-2.0-APPLICATOR-E-080F110OV



TE Part # 2-2150158-2
 OCEAN-2.0-APPLICATOR-E-080F110OVA



TE Part # 2150158-1
 OCEAN-2.0-APPLICATOR-E-080F110OV



TE Part # 2150158-2
 OCEAN-2.0-APPLICATOR-E-080F110OVA



TE Part # 2376595-2
 250 FASTON PCB TAB TPBR



TE Part # 7-2150158-1
 OCEAN-2.0-APPLICATOR-E-080F110OV



TE Part # 7-2150158-2
 OCEAN-2.0-APPLICATOR-E-080F110OVA



TE Part # 7-2150158-7
 OCEAN_2.0_SPARE_PART_KIT-080F110OV



TE Part # 539743-2
 DIE F2.8FF TAB



TE Part # 2376591-3
 250 FASTON PCB TAB TPBR LP

Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(143)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(144)



Quick Disconnects(456)




Splices(4)

Customers Also Bought



TE Part #60413-1
 FF 250 REC 22-18AWG TPBR



TE Part #60798-4
 SHUR PLUG 180 RECEPTACLE 18-14
 AWG TPBR



TE Part #61867-2
 RING CRIMP 18-14 AWG TPBR



TE Part #776533-2
 AMPSEAL 16 HOUSINGS



TE Part #DTM04-6P-E003
 REC, 6P, GRY, N, CAP

Documents

Product Drawings

[250 FASTON,REC.,20-17 AWG,TPPB](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_160915-2_J.2d_dxf.zip](#)

English

[3D PDF](#)



3D

Customer View Model

[ENG_CVM_CVM_160915-2_J.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_160915-2_J.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English