1744418-3 ACTIVE

Economy Power 2.5

TE Internal #: 1744418-3

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, .098 in [2.5]

mm] Centerline, Fully Shrouded, Tin, Through Hole - Solder,

Economy Power 2.5

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 3

Number of Rows: 1

Centerline (Pitch): 2.5 mm [.098 in]
PCB Mount Orientation: Vertical

Features

Product Type Features

| Connector System | Wire-to-Board |
|-----------------------------------|-----------------------|
| Header Type | Fully Shrouded |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| PCB Connector Assembly Type | PCB Mount Header |

Configuration Features

| Connector Contact Load Condition | Fully Loaded |
|----------------------------------|--------------|
| Number of Positions | 3 |
| Number of Rows | 1 |
| PCB Mount Orientation | Vertical |

Electrical Characteristics

| Operating Voltage | 250 VAC |
|-------------------|---------|
| Operating voltage | 230 VAC |

Body Features

| Primary Product Color | Natural | |
|-----------------------|---------|--|



| Contact Features | |
|--|----------------------------|
| Contact Layout | Inline |
| Mating Pin Diameter | .6 mm[.024 in] |
| Contact Mating Area Plating Material Thickness | 2 – 5 μm[80 – 200 μin] |
| Contact Mating Area Plating Material Finish | Bright |
| Contact Base Material | Copper Alloy |
| Contact Mating Area Plating Material | Tin |
| Contact Type | Pin |
| Contact Current Rating (Max) | 4.2 A |
| ermination Features | |
| Round Termination Post & Tail Diameter | .6 mm[.024 in] |
| Termination Post & Tail Length | 3.4 mm[.133 in] |
| Termination Method to Printed Circuit Board | Through Hole - Solder |
| Mechanical Attachment | |
| PCB Mount Alignment Type | Boss |
| Mating Alignment Type | Polarization |
| Mating Retention | With |
| Panel Mount Feature | Without |
| PCB Mount Retention Type | Kinked |
| Connector Mounting Type | Board Mount |
| Mating Alignment | With |
| PCB Mount Alignment | With |
| PCB Mount Retention | With |
| Housing Features | |
| Housing Material | Nylon |
| Centerline (Pitch) | 2.5 mm[.098 in] |
| Dimensions | |
| Connector Length | 12.5 mm[.492 in] |
| Connector Height | 8.8 mm[.346 in] |
| Jsage Conditions | |
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
| | |

Operation/Application



| Circuit Application | Power & Signal |
|------------------------|----------------|
| Industry Standards | |
| Glow Wire Rating | Glow Wire |
| UL Flammability Rating | UL 94V-0 |
| Packaging Features | |
| Packaging Quantity | 600 |
| Packaging Type | Bag |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









PIN 2,3



Also in the Series | Economy Power 2.5



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(210)



PCB Latches, Locks & Retainers(49)



Rectangular Power Connectors(43)



Wire-to-Board Connector Assemblies & Housings(216)



Wire-to-Board Connector Contacts(6)

Customers Also Bought



TE Part #2132230-4 EP2.5 Shrouded HDR ASSY 4P VER



TE Part #1744417-4 4 POS EP 2.5 HSG, GLOW WIRE




TE Part #1744418-6 6 POS EP 2.5 HDR, GLOW WIRE



TE Part #1744417-5 5 POS EP 2.5 HSG, GLOW WIRE



TE Part #2232983-1 EP 2.5 LIF RCPT CONTACT, 24-20 AWG



TE Part #1217566-1 250 FASTON,PCB TAB,TCBR



TE Part #1744418-9 9 POS EP 2.5 HDR, GLOW WIRE



TE Part #1-1969570-2 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5



Documents

Product Drawings

3 POS EP 2.5 HDR, GLOW WIRE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1744418-3_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1744418-3_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1744418-3_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773461-6_EP2.5_Connector_Series

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

VDE Certificate

English