

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

LOC

DIST

REVISIONS

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
G	REVISED	ECR-14-018500	18DEC2014	TS	YF

WIRE RANGE ID MARK
("S" SIZE MARK)
(STAMPED ON BOTTOM)

端子識別マーク "S"
(底面に刻印)

断面 A-A
SECT A-A

断面 B-B
SECT B-B

断面 A-A
SECT A-A
(175026のみ適用)
(ONLY 175026)

断面 B-B
SECT B-B
(175026のみ適用)
(ONLY 175026)

1. 製品規格 ; 108-5216, 108-5231, 108-5264

2. 取付適用規格 ; 114-5091

3. 部分金めっき (接触面のみ)

4. 識別用金めっき (全周)

5. 部分金めっき (両側のみ)

1. SPEC; 108-5216, 108-5231, 108-5264

2. APPLICATION SPEC; 114-5091

3. SELECTIVE GOLD PLATING (ONLY CONTACT SIDE)

4. GOLD PLATING FOR DISCERNMENT (ALL AROUND)

5. SELECTIVE GOLD PLATING (ONLY BOTH SIDES OF THE BOX)

WIRE RANGE
AVS 0.2~0.3mm²
(AWG#24-#22)

INSULATION DIA.
1.4~1.9 mmφ

	部分金めっき SELECTIVE GOLD	黄銅 板厚0.3 BRASS ±0.3	1-173630-2
175026-7	部分金めっき SELECTIVE GOLD	リン青銅 板厚0.3 PHOS BRO. ±0.3	173630-7
175026-6	錫めっき済み PRE-TINNED	銅合金 板厚0.3 COPPER ALLOY ±0.3	173630-6
	部分金めっき SELECTIVE GOLD	黄銅 板厚0.3 BRASS ±0.3	173630-2
175026-1	錫めっき済み PRE-TINNED	黄銅 板厚0.3 BRASS ±0.3	173630-1
バラ端子型番 L/P NUMBER	仕上 FINISH	材料 MATERIAL	型番 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

TOLERANCE UNLESS
OTHERWISE SPECIFIED:
一般公差

0 < x ≤ 10 : ±0.2
10 < x ≤ 30 : ±0.25
30 < x ≤ 100 : ±0.3
ANGLE ; ±3°

0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±-
4 PLC ±-
ANGLES ±-

MATERIAL
SEE TABLE

FINISH
SEE TABLE

DWN 9/28'87

CHK T.SAGAWA

10/6'87

M.MATSUSAKA

APVD 10/7'87

M.NOBUCHI

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

STE TE Connectivity

070 SERIES RECEPTACLE CONTACT

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=173630	-

SCALE 5:1 SHEET 1 of 1 REV G

1470-19 (3/11)