## AMP | Multilock Connector System


TE Internal #: 174933-2

Housing for Female Terminals, Wire-to-Wire, 12 Position, Black, Signal, Cable Mount (Free-Hanging), Multilock Connector System

View on TE.com >



Connectors > Automotive Connectors > Connector Housings > MULTILOCK, CONNECTOR HOUSING



Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.8 mm [.071 in]
Connector System: Wire-to-Wire

Number of Positions: 12

Sealable: No

## All MULTILOCK, CONNECTOR HOUSING (576)

# **Features**

# **Product Type Features**

Connector & Housing Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	No
Hybrid Connector	No
Configuration Features	
Number of Positions	12
Number of Rows	2
Body Features	
Body Material	PBT
Primary Product Color	Black
Contact Features	
Contact Size	1.8mm

Receptacle

Without

1.8 mm[.071 in]

Contact Type

Mating Tab Width

Mounting Feature

Mechanical Attachment



Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Dimensions	
Product Width	18.2 mm[.717 in]
Product Length	32.7 mm[1.29 in]
Product Height	31.4 mm[1.24 in]
Row-to-Row Spacing	3 mm[.118 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	50
Other	
Connector Position Assurance Capable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**









# Also in the Series | Multilock Connector System



Automotive Connector Caps & Covers (16)



Automotive Connector EMC Shielding (1)



Automotive Connector Locks & Position Assurance(2)



Automotive Housings(575)



Automotive Seals & Cavity Plugs(2)



Automotive Terminals(141)



Insertion & Extraction Tools(6)



Other Automotive Connector Accessories(9)





# Customers Also Bought



















# **Documents**

Product Drawings
070 MLC W-W CAP HSG 12P B

English

**CAD Files** 

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_174933-2\_K.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_174933-2\_K.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_174933-2\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

MULTILOCK Connector System

English

**Product Specifications** 

**Product Specification** 

Japanese