1744417-3 ACTIVE

Economy Power 2.5

TE Internal #: 1744417-3

Housing, Receptacle, Wire-to-Board, 3 Position, 2.5 mm [.098 in] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable,

Economy Power 2.5

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 3

Centerline (Pitch): 2.5 mm [.098 in]

Features

Product Type Features

Trouder Type Fourth Services	
Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 VAC
Contact Features	
Contact Layout	Inline
Contact Type	Socket



Termination Features

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Latch
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Entry Configuration	Both Ends Closed
Housing Material	Nylon
Centerline (Pitch)	2.5 mm[.098 in]
Housing Color	Natural
Dimensions	
	9.8 mm[.385 in]
Dimensions	9.8 mm[.385 in] 5.7 mm[.224 in]
Dimensions Connector Length	
Dimensions Connector Length Connector Height	
Dimensions Connector Length Connector Height Usage Conditions	5.7 mm[.224 in]
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range	5.7 mm[.224 in]
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range Operation/Application	5.7 mm[.224 in] -55 – 105 °C[-67 – 221 °F]
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range Operation/Application Circuit Application	5.7 mm[.224 in] -55 – 105 °C[-67 – 221 °F]
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	5.7 mm[.224 in] -55 – 105 °C[-67 – 221 °F] Power
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards Glow Wire Rating	5.7 mm[.224 in] -55 – 105 °C[-67 – 221 °F] Power Glow Wire
Dimensions Connector Length Connector Height Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards Glow Wire Rating UL Flammability Rating	5.7 mm[.224 in] -55 – 105 °C[-67 – 221 °F] Power Glow Wire

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





EP 2.5 TPA Retainer, 3 Pos



EP 2.5 RCPT CONTACT, 24-20 AWG















TE Part # 1744446-3 Hdr Assy, EP 2.5 RA, 3 Pos., GW



TE Part # 1-2299683-3 EP2.5 HDR 3P VERT W/O BOSS, TAPING,RED



TE Part # 2299683-3
EP2.5 HDR 3P VERT W/O BOSS,
TAPING





Also in the Series | Economy Power 2.5



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(210)



PCB Latches, Locks & Retainers(49)



Rectangular Power Connectors(43)



Wire-to-Board Connector Assemblies & Housings(216)




Wire-to-Board Connector Contacts(6)


Customers Also Bought




TE Part #179939-1
POWER D/LOCK PLUG HSG 4P /6.5



TE Part #154717-7
PL 250 REC TERMINAL 13-11 AWG
PTPPB



TE Part #927852-7
PL 250 REC TERMINAL 20-17 AWG
PTPPB



TE Part #170224-2 250 FASTON,REC.,16-10 AWG,BR











Documents

Product Drawings

3 POS EP 2.5 HSG, GLOW WIRE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1744417-3_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1744417-3_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1744417-3_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773461-6_EP2.5_Connector_Series

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_1744417-3_032220181011_dmtec

English

MD_1744417-3_032220181011_dmtec

English

Agency Approvals

VDE Certificate

English