

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **1721301108**
Status: **Active**
Overview: Impel and Impel Plus Backplane Solutions
Description: Impel 90 Ohm 6 Pair Right-Angle Header, 1.90mm Pitch, Unguided, 10 Columns, Open Endwalls, 120 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm

Documents:

3D Model	Application Specification AS-171320-992-001 (PDF)
3D Model (PDF)	Packaging Specification PK-78888-311-001 (PDF)
Drawing (PDF)	Symbol Footprint Data SYM-172130-1108 (PDF)
Product Specification PS-171320-999-001 (PDF)	Symbol Footprint Data SYM-172130-1208 (PDF)
Application Specification AS-171320-990-001 (PDF)	RoHS Certificate of Compliance (PDF)
Application Specification AS-171320-991-001 (PDF)	

Agency Certification

UL E29179

General

Product Family	Backplane Connectors
Series	172130
Application	Backplane, Coplanar
Application Tooling Documents	TM-622018899
Component Type	PCB Header
Overview	Impel and Impel Plus Backplane Solutions
Product Name	Impel
UPC	887191624464

Physical

Circuits (Loaded)	120
Circuits (maximum)	120
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Nickel, Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	94.909/g
Number of Columns	10
Number of Pairs	6
Number of Rows	12
Orientation	Right Angle
PC Tail Length	1.30mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.00mm
Packaging Type	Tray
Pitch - Mating Interface	1.90mm
Pitch - Termination Interface	1.90mm
Plating min - Mating	0.762µm
Temperature Range - Operating	-55° to +85°C

Electrical

Current - Maximum per Contact 0.75A



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[172130 Series](#)

Mates With

Impel Right-Angle Daughtercard
[1714001020](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Impel Daughter Card [622018919](#)

Press-In Tool

Installation Press- [622019005](#)

in Tool for Impel

Plus 1.90mm Pitch

Daughtercard

Unguided Assembly

and RAM Unguided

Assembly (6-Pair by

10 Column)

Data Rate	40.0 Gbps
Impedance	90Ω
Shield Type	Full Shield
Voltage - Maximum	150V AC (RMS)/DC

Solder Process Data

Lead-free Process Capability	N/A
------------------------------	-----

Material Info**Reference - Drawing Numbers**

Application Specification	AS-171320-990-001, AS-171320-991-001, AS-171320-992-001
Packaging Specification	PK-78888-311-001
Product Specification	PS-171320-999-001
Sales Drawing	SD-172130-0001-001
Symbol/Footprint Data	SYM-172130-1108, SYM-172130-1208

This document was generated on 07/21/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION