




STANDARD RING TONGUE



Material: Copper




Krimptite®



Insulkrimp®
(PVC Insulation)


| Wire Range AWG (mm ²) | Stud Size S | Maximum Width W | Minimum Clearance C | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L |
|--------------------------------------|-------------|--------------------|------------------------|--------------------------|-------------------------|---------------------|--------------------------|-------------------------|---------------------|
| 10-12 (5.00-3.30) | 5-6 (3-3.5) | 7.40 (.292) | 7.80 (.306) | 19069-0230 | 19069-0232 | 18.80 (.741) | 19070-0143 | 19070-0144 | 26.20 (1.032) |
| | | 9.80 (.385) | 7.70 (.303) | 19069-0202 | | 19.90 (.785) | 19070-0119 | 19070-0120 | 27.30 (1.076) |
| | 8 (4) | 7.40 (.292) | 7.80 (.306) | 19069-0233 | 19069-0235 | 18.80 (.741) | 19070-0145 | 19070-0146 | 26.20 (1.032) |
| | | 9.80 (.385) | 7.70 (.303) | 19069-0205 | 19069-0208 | 19.90 (.785) | 19070-0121 | 19070-0122 | 27.30 (1.076) |
| | 10 (-) | 9.80 (.385) | 7.70 (.303) | 19069-0209 | 19069-0212 | 19.90 (.785) | 19070-0123 | 19070-0125 | 27.30 (1.076) |
| | | 13.70 (.540) | 10.00 (.393) | 19069-0217 | 19069-0218 | 24.20 (.952) | 19070-0130 | 19070-0131 | 31.60 (1.243) |
| | | 15.20 (.598) | 14.40 (.566) | 19069-0236 | | 26.80 (1.056) | | | |
| | 1/4 (6) | 13.70 (.540) | 10.00 (.393) | 19069-0219 | 19069-0221 | 24.20 (.952) | 19070-0132 | 19070-0133 | 31.60 (1.243) |
| | | 15.20 (.598) | 14.40 (.566) | 19069-0238 | 19069-0240 | 26.80 (1.056) | 19070-0150 | 19070-0151 | 34.20 (1.347) |
| | 5/16 (8) | 13.70 (.540) | 10.00 (.393) | 19069-0223 | 19069-0225 | 24.20 (.952) | 19070-0136 | 19070-0137 | 31.60 (1.243) |
| | | 15.20 (.598) | 14.40 (.566) | 19069-0244 | 19069-0246 | 26.80 (1.056) | 19070-0155 | 19070-0156 | 34.20 (1.347) |
| | 3/8 (9) | 15.20 (.598) | 14.40 (.566) | 19069-0241 | 19069-0243 | 26.80 (1.056) | 19070-0153 | 19070-0154 | 34.20 (1.347) |
| | | 19.30 (.760) | 15.50 (.611) | 19069-0196 | 19069-0145 | 32.50 (1.280) | | | 39.90 (1.571) |
| | 7/16 (11) | 19.30 (.760) | 15.50 (.611) | 19069-0198 | 19069-0146 | 32.50 (1.280) | 19070-0115 | 19070-0116 | 39.90 (1.571) |
| | 1/2 (12) | 19.30 (.760) | 15.50 (.611) | 19069-0192 | 19069-0194 | 32.50 (1.280) | 19070-0109 | 19070-0110 | 39.90 (1.571) |



Material: Copper



Versakrimp™



Avikrimp®
(Nylon Insulation)

| Wire Range AWG (mm ²) | Stud Size S | Maximum Width W | Minimum Clearance C | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L | Loose Piece Order No. | Mylar Tape Order No. | Expanded Flare Order No.* | Expanded Flare on Mylar Tape Order No.* | Maximum Length L |
|--------------------------------------|-------------|--------------------|------------------------|--------------------------|-------------------------|---------------------|--------------------------|-------------------------|------------------------------|---|---------------------|
| 10-12 (5.00-3.30) | 5-6 (3-3.5) | 7.40 (.292) | 7.80 (.306) | 19193-0128 | 19193-0129 | 18.80 (.741) | 19073-0216 | 19073-0218 | 19073-0220 | 19073-0221 | 27.00 (1.047) |
| | | 9.80 (.385) | 7.70 (.303) | 19193-0103 | 19193-0105 | 19.90 (.785) | 19073-0160 | 19073-0162 | 19073-0163 | 19073-0164 | 27.70 (1.091) |
| | 8 (4) | 7.40 (.292) | 7.80 (.306) | 19193-0130 | 19193-0131 | 18.80 (.741) | 19073-0222 | 19073-0224 | 19073-0225 | 19073-0226 | 27.00 (1.047) |
| | | 9.80 (.385) | 7.70 (.303) | 19193-0106 | 19193-0108 | 19.90 (.785) | 19073-0165 | 19073-0167 | 19073-0168 | 19073-0169 | 27.70 (1.091) |
| | 10 (-) | 9.80 (.385) | 7.70 (.303) | 19193-0109 | 19193-0111 | 19.90 (.785) | 19073-0170 | 19073-0172 | 19073-0173 | 19073-0174 | 27.70 (1.091) |
| | | 13.70 (.540) | 10.00 (.393) | 19193-0114 | 19193-0115 | 24.20 (.952) | 19073-0179 | 19073-0180 | 19073-0181 | 19073-0184 | 32.00 (1.258) |
| | | 15.20 (.598) | 14.40 (.566) | | | | 19073-0227 | 19073-0228 | 19073-0229 | 19073-0230 | 34.60 (1.362) |
| | 1/4 (6) | 13.70 (.540) | 10.00 (.393) | 19193-0116 | 19193-0118 | 24.20 (.952) | 19073-0188 | 19073-0190 | 19073-0191 | 19073-0194 | 32.00 (1.258) |
| | | 15.20 (.598) | 14.40 (.566) | 19193-0134 | 19193-0135 | 26.80 (1.056) | 19073-0231 | 19073-0232 | 19073-0233 | 19073-0234 | 34.60 (1.362) |
| | 5/16 (8) | 13.70 (.540) | 10.00 (.393) | 19193-0120 | 19193-0122 | 24.20 (.952) | 19073-0200 | 19073-0201 | 19073-0202 | 19073-0205 | 32.00 (1.258) |
| | | 15.20 (.598) | 14.40 (.566) | 19193-0141 | 19193-0142 | 26.80 (1.056) | 19073-0242 | 19073-0243 | 19073-0244 | 19073-0245 | 34.60 (1.362) |
| | 3/8 (9) | 15.20 (.598) | 14.40 (.566) | 19193-0137 | 19193-0139 | 26.80 (1.056) | 19073-0236 | 19073-0237 | 19073-0238 | 19073-0239 | 34.60 (1.362) |
| | | 19.30 (.760) | 15.50 (.611) | 19193-0097 | | 32.50 (1.280) | | | | | |
| | 7/16 (11) | 19.30 (.760) | 15.50 (.611) | 19193-0099 | 19193-0100 | 32.50 (1.280) | | | | | |
| | 1/2 (12) | 19.30 (.760) | 15.50 (.611) | 19193-0094 | 19193-0095 | 32.50 (1.280) | 19073-0145 | 19073-0146 | 19073-0147 | | 40.30 (1.586) |

* For use with heavier wire insulation. Maximum wire insulation (.255") 6.50mm.