



		Krimptite®				Insulkrimp® (PVC Insulation)		
		Material: Copper Thickness: 0.80mm (.032") max.						
Wire Range AWG	Dimension		Loose Piece Order No.	Mylar Tape Order No.	Length L (in.)	3.60 (.140) Max. Wire Insul. Dia.	4.40 (.175) Max. Wire Insul. Dia.	Max. Length L
	Barrel Length B	Diameter D				Loose Piece Order No.	Loose Piece Order No.	
18-22 (0.80-0.35)	.254	.180	19033-0001		.754	19034-0002		24.10 (.950)
18-22 (0.80-0.35)	.254	.156	19033-0003	19033-0004	.694	19034-0005		22.60 (.890)
14-16 (2.00-1.30)	.254	.180	19033-0005	19033-0006	.754		19034-0007	24.10 (.950)
14-16 (2.00-1.30)	.254	.156	19033-0007	19033-0008	.694		19034-0009	22.60 (.890)

Note: For open barrel strip products, please contact factory

		Avikrimp® (Molded Nylon Insulation)				Avikrimp (Extruded Nylon Insulation)						
		Material: Copper Thickness: 0.80mm (.032") max.										
Wire Range AWG	Dimension		3.60 (.140) Max. Wire Insul. Dia.		4.30 (.170) Max. Wire Insul. Dia.		Max. Length L	3.60 (.140) Max. Wire Insul. Dia.		4.30 (.170) Max. Wire Insul. Dia.		Max. Length L
	Barrel Length B	Diameter D	Loose Piece Order No.	Mylar Tape Order No.	Loose Piece Order No.	Mylar Tape Order No.		Loose Piece Order No.	Mylar Tape Order No.	Loose Piece Order No.	Mylar Tape Order No.	
18-22 (0.80-0.35)	.254	.180	19035-0001	19035-0002			24.10 (.948)	19036-0001	19036-0002			24.30 (.957)
18-22 (0.80-0.35)	.254	.156	19035-0003	19035-0004			22.60 (.888)	19036-0003	19036-0005			22.80 (.897)
14-16 (2.00-1.30)	.254	.180			19035-0005	19035-0008	24.10 (.948)			19036-0006	19036-0007	24.30 (.957)
14-16 (2.00-1.30)	.254	.156			19035-0009	19035-0012	22.60 (.888)			19036-0008	19036-0009	22.80 (.897)

Note: For open barrel strip products, please contact factory