178327-2 - ACTIVE

Dynamic Series | Dynamic 3000 Series

TE Internal #: 178327-2 PCB Mount Header, Vertical, Wire-to-Board, 16 Position, .15 in [3.81 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 3000 Series

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles > Header Assembly: Wire-to-Board, 15A, gold or tin plated



Connector System: Wire-to-Board Number of Positions: 16

Number of Rows: 2

Centerline (Pitch): 3.81 mm [.15 in]

PCB Mount Orientation: Vertical

All Header Assembly: Wire-to-Board, 15A, gold or tin plated (120)



Features

Product Type Features

Connector System	Wire-to-Board		
Header Type	Fully Shrouded		
Sealable	No		
Connector & Contact Terminates To	Printed Circuit Board		
PCB Connector Assembly Type	PCB Mount Header		
Configuration Features			
Number of Positions	16		
Number of Rows	2		
PCB Mount Orientation	Vertical		
Body Features			
Primary Product Color	Black		
Contact Features			

PCB Mount Header, Vertical, Wire-to-Board, 16 Position, .15 in [3.81 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 3000 Series



Contact Mating Area Plating Material Thickness	.38 μm[15 μin]	
Contact Mating Area Plating Material	Gold	
Contact Type	Pin	
Contact Current Rating (Max)	8 A	
Termination Features		
Termination Method to Printed Circuit Board	Through Hole - Solder	
Mechanical Attachment		
Mating Alignment Type	Polarization	
Mating Retention	With	
PCB Mount Retention Type	Retention Leg	
Connector Mounting Type	Board Mount	
Mating Alignment	With	
PCB Mount Alignment	Without	
PCB Mount Retention	With	
Housing Features		
Housing Material	Polyester GF	
Centerline (Pitch)	3.81 mm[.15 in]	

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Type	Box, Tube
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016 EU REACH Regulation (EC) No. 1907/2006	No Restricted Materials Above Threshold

PCB Mount Header, Vertical, Wire-to-Board, 16 Position, .15 in [3.81 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 3000 Series



Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Not Low Halogen - contains Br or Cl > 900

Halogen Content

Solder Process Capability

Wave solder capable to 265°C

ppm.

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | Dynamic 3000 Series

A Contraction of the second se			
Connector Contacts(3)	Insertion & Extraction Tools(1)	PCB Connector Keying(1)	PCB Connector Mounting(8)

PCB Mount Header, Vertical, Wire-to-Board, 16 Position, .15 in [3.81 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 3000 Series







Customers Also Bought



Header Assembly: Wire-to-Board, 15A, gold or tin plated

Header Assembly: Wire-to-Board, 15A, gold or tin plated

Documents

Product Drawings 16-P POST HDR D-3100D VERT .38

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_178327-2_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_178327-2_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_178327-2_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

C For support call+1 800 522 6752

PCB Mount Header, Vertical, Wire-to-Board, 16 Position, .15 in [3.81 mm] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 3000 Series



Datasheets & Catalog Pages

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

Japanese

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

English

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals TUV Certificate

English