178325-5 ✓ ACTIVE

Dynamic Series | Dynamic 3000 Series

TE Internal #: 178325-5

PCB Mount Header, Vertical, Wire-to-Board, 10 Position, .15 in [3.81

mm] Centerline, Fully Shrouded, Tin, Through Hole - Solder,

Dynamic 3000 Series

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Header Assembly: Wire-to-Board, 15A, gold or tin plated











Connector System: Wire-to-Board

Number of Positions: 10

Number of Rows: 2

Centerline (Pitch): 3.81 mm [.15 in]
PCB Mount Orientation: Vertical

All Header Assembly: Wire-to-Board, 15A, gold or tin plated (120)

Features

Product Type Features

rioduct Type reatures	
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Positions	10
Number of Rows	2
PCB Mount Orientation	Vertical
Body Features	
Primary Product Color	Black



Contact Mating Area Plating Material Thickness	2 μm[80 μin]
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	15 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	With
PCB Mount Retention Type	Retention Leg
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
	With
PCB Mount Alignment	
PCB Mount Alignment PCB Mount Retention	
PCB Mount Alignment PCB Mount Retention Housing Features	With
PCB Mount Alignment PCB Mount Retention Housing Features Housing Material	With Polyester GF
PCB Mount Alignment PCB Mount Retention Housing Features Housing Material Centerline (Pitch)	With Polyester GF
PCB Mount Alignment PCB Mount Retention Housing Features Housing Material Centerline (Pitch) Usage Conditions	With Polyester GF 3.81 mm[.15 in]
PCB Mount Alignment PCB Mount Retention Housing Features Housing Material Centerline (Pitch) Usage Conditions Operating Temperature Range	With Polyester GF 3.81 mm[.15 in]
PCB Mount Alignment PCB Mount Retention Housing Features Housing Material Centerline (Pitch) Usage Conditions Operating Temperature Range Operation/Application	With Polyester GF 3.81 mm[.15 in] -55 – 105 °C[-67 – 221 °F]

Product Compliance

Packaging Features

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold

Box, Tube



EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2022

(224)

Candidate List Declared Against: JAN 2022

(223)

SVHC > Threshold: Not Yet Reviewed

Halogen Content Not Low Halogen - contains Br or Cl > 900

ppm.

Solder Process Capability Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | Dynamic 3000 Series









Insertion & Extraction Tools(1)

PCB Connector Keying(1)

07/22/2022 04:52AM | Page 3





PCB Headers & Receptacles(283)




PCB Terminal Blocks(25)



Standard Rectangular Connectors(2)



Wire-to-Board Connector Assemblies & Housings(152)



Customers Also Bought



TE Part #178305-5 Header Assembly: Wire-to-Board, 15A, gold or tin plated



TE Part #2-178128-3
DYNAMIC 3200 REC HSG 3P (SGL)



TE Part #2-1437538-1 832-AG10D=SOCKET ASSY



TE Part #171825-7 V-TYPE E.I.S.CONN. 7P ASSY



Documents

Product Drawings

DYNAMIC D3100D HDR V 10P ASSY SN

Japanese

CAD Files

3D PDF

English

Customer View Model ENG_CVM_178325-5_E.2d_dxf.zip



English

Customer View Model

ENG_CVM_178325-5_E.3d_igs.zip

English

Customer View Model

ENG_CVM_178325-5_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

Japanese

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

English

Product Specifications

Product Specification

English

Product Environmental Compliance

MD_178325-5_11102017610_dmtec

English

MD_178325-5_11102017610_dmtec

English

Agency Approvals

TUV Certificate

English