

EPIC® H-B 10 TBF

Housing design H-B. The industry standard.

The low metal housing with 2 double levers and a direct cable entry is ideal for investment construction applications.

Info

Double lever version with 2 levers for increased safety









Waterproof



Robust



Mechanical resistance



Mechanical and plant engineering



Kompletterande automationskomponenter från Lapp

Benefits

The smallest housing with single and double lever. The right housing is available for every application

Application range

Plant engineering Light & sound technology Plastics industry

Product features

Cable coupler hood, low version Dual levers

Last Update (06.06.2019)
©2019 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



EPIC® H-B 10 TBF

Straight cable entry
Versions with / without neck

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

JL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-B 10 TBF

М PG Pieces / PU Article number Article description Neck H-B housing: cable coupler hood (straight cable entry, double lever) 10 10046000 H-B 10 TBF 16 16 yes H-B 10 TBF 21 21 10 70040200 yes 20 19046000 H-B 10 TBF M20 10 25 H-B 10 TBF M25 10 79040200

Last Update (06.06.2019)

©2019 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16