TE Internal #: 1761426-3

Card Edge Power Connectors, Board-to-Board, 26 Position, .1 in / .

3 in [7.62 mm] Centerline, Printed Circuit Board, Power, 6 Power

Positions

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Card Edge Power Connectors



Connector System: Board-to-Board

Number of Positions: 26

Centerline (Pitch): 7.62 mm [.1 in, .3 in]

Connector & Contact Terminates To: Printed Circuit Board

Contact Current Rating (Max): 3 A

Features

Product Type Features

Housing Type	Receptacle
Connector System	Board-to-Board
Contact Type	Socket
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Keying & Polarized Position Locations	0
PCB Mount Orientation	Vertical
Number of Positions	26
Number of Power Positions	6
Number of Signal Positions	20
Number of Dual Positions	2
ranie di Baari dolliono	3
Row-to-Row Spacing	4.85 mm[.191 in]



Contact Features

Contact Features	
Contact Termination Area Plating Finish	Matte
Contact Mating Area Plating Material Thickness	.38 μm[15 μin]
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	3 A
Contact Mating Area Plating Material	Gold
Contact Termination Area Plating Material	Tin
Contact Termination Area Plating Thickness	2.54 µm
Termination Features	
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment	Without
PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail
Connector Mounting Type	Board Mount
Mating Alignment	With
Mating Retention	Without
Mating Alignment Type	Keyed
Housing Features	
End Caps	Without
Centerline (Pitch)	7.62 mm[.1 in][.3 in]
Housing Color	Black
Housing Material	Polyester GF
Dimensions	
Power Contact Centerline	7.62 mm[.3 in]
Height	15.49 mm[.61 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power



Industry Standards

UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Package
Packaging Quantity	1
Other	
Position Locations Omitted	0

Printed Circuit Board

Product Compliance

For Use With

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought




BNC Right Angle M Jack RF Connector, 50 Ohm, Bayonet Coupling Mechanism













TE Part #9-146258-0



TE Part #2042274-2 CODING



TE Part #5-532955-4





Documents

Product Drawings

CONNECTOR ASSY, ULTRA HIGH CURRENT CARD

English

CAD Files

Customer View Model ENG_CVM_CVM_1761426-3_B.2d_dxf.zip

English

3D PDF



3D

Customer View Model

ENG_CVM_CVM_1761426-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1761426-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

POWER_CONNECTORS_CATALOG_SEC03_CARD_EDGE

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English