



Rated cross-section ≤ 4.0 mm²



LL 9.5/90

new



Technische Daten		VDE	UL	CSA
Rated voltage	V	630*	300	300
Rated current	A	32	30	30
Clamping range max.	mm ² /AWG	4.0	10	10



*Overvoltage category III / Pollution severity 3
Additional technical data see page 62

Solder pin length **5.0 mm** **5.0 mm**

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
2	LL 9.5/2/90	1724680000	1724700000	50
3	LL 9.5/3/90	1724690000	1724710000	50

TOP4GS 6.35/90



Technische Daten		VDE	UL	CSA
Rated voltage	V	320*	300	300
Rated current	A	36	30	30
Clamping range max.	mm ² /AWG	6.0	10	10

*Overvoltage category III / Pollution severity 3
Additional technical data see page 63



Solder pin length **3.5 mm** **3.5 mm**

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
2	TOP4GS2/90	1401760000	1786110000	100
3	TOP4GS3/90	1650300000	0265910000	100
4	TOP4GS4/90	1786030000	1536210000	50
5	TOP4GS5/90	1786040000	0308410000	50
6	TOP4GS6/90	1786050000	1786120000	50
7	TOP4GS7/90	1786060000	1786130000	50
8	TOP4GS8/90	1667910000	1786140000	50
9	TOP4GS9/90	1786070000	1786150000	50
10	TOP4GS10/90	1786080000	1786160000	50
11	TOP4GS11/90	1786090000	1786170000	50
12	TOP4GS12/90	1786100000	1786180000	50

Accessories	Page
Marking	41
Fixing	-
Miscellaneous	45

TOP4GS 6.35/180



Technische Daten		VDE	UL	CSA
Rated voltage	V	320*	300	300
Rated current	A	36	30	30
Clamping range max.	mm ² /AWG	6.0	10	10

*Overvoltage category III / Pollution severity 3
Additional technical data see page 63

Solder pin length **3.5 mm** **3.5 mm**

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
2	TOP4GS2/180	1786190000	1786300000	100
3	TOP4GS3/180	1786200000	1786310000	100
4	TOP4GS4/180	1786210000	1786320000	50
5	TOP4GS5/180	1786220000	1786330000	50
6	TOP4GS6/180	1786230000	1786340000	50
7	TOP4GS7/180	1786240000	1786350000	50
8	TOP4GS8/180	1786250000	1786360000	50
9	TOP4GS9/180	1786260000	1786370000	50
10	TOP4GS10/180	1786270000	1786380000	50
11	TOP4GS11/180	1786280000	1786390000	50
12	TOP4GS12/180	1786290000	1786400000	50

Accessories	Page
Marking	41
Fixing	-
Miscellaneous	45

Rated cross-section ≤ 4.0 mm²