



FULLY INSULATED PIGGYBACK QD'S

- Fully insulated with a rigid nylon housing
- Expanded flare version makes inserting dual wires easier
- Avikrimp version has a metal grip sleeve for extra insulation support



Insulkrimp Standard Flare

Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
22-18 AWG (0.3-1.0)	.250 x .032	19013-0001	19013-0002	0.140 (3.56)	0.38 (9.65)	0.86 (21.84)
16-14 AWG (1.2-2.0)	.250 x .032	19013-0005	19013-0006	0.165 (4.19)	0.38 (9.65)	0.86 (21.84)
12-10 AWG (3.0-6.0)	.250 x .032	19013-0018	19013-0016	0.280 (7.11)	0.38 (9.65)	1.02 (25.91)

Insulkrimp Expanded Flare


Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
22-18 AWG (0.3-1.0)	.250 x .032	19013-0003	19013-0004	0.230 (5.84)	0.38 (9.65)	0.94 (23.88)
16-14 AWG (1.2-2.0)	.250 x .032	19013-0007	19013-0008	0.260 (6.60)	0.38 (9.65)	0.94 (23.88)
12-10 AWG (3.0-6.0)	.250 x .032	19013-0018	19013-0016	0.280 (7.11)	0.38 (9.65)	1.02 (25.91)

Avikrimp

Wire Range	Tab Size	Loose Piece Order No.	Mylar Tape Order No.	Max. Wire Insul. Dia.	Max. Width	Max. Length
18-22 AWG (0.8-0.35)	.250 x .032	19602-1100	19602-1101	0.120 (3.05)	0.39 (9.91)	0.88 (22.35)
14-16 AWG (2.00-1.30)	.250 x .032	19602-1200	19602-1201	0.141 (3.58)	0.39 (9.91)	0.88 (22.35)
10-12 AWG (5.00-3.30)	.250 x .032	19602-1300	19602-1301	0.233 (5.92)	0.38 (9.78)	1.02 (25.91)

OPEN BARREL STRIP PIGGYBACK QD'S


- Open barrel strip version allows for rapid terminations



Wire Range	Tab Size	Max. Wire Insul. Dia.	Brass Order No.	Tin Plated Order No.	Max. Length
22-16 AWG (0.3-1.2)	.250 x .032	.145 (3.68)	19014-0001	19014-0002	.802 (20.4)
18-12 AWG (1.0-3.0)	.250 x .032	.180 (4.57)	19014-0003	19014-0004	.802 (20.4)

OPEN BARREL STRIP LOCKING QD'S

- Locking lance sets the QD into place within the housing
- Fits into industry standard housings



Wire Range	Tab Size	Max. Wire Insul. Dia.	Brass Order No.	Tin Plated Order No.	Max. Length
22-16 AWG (0.3-1.2)	.250 x .032	.145 (3.68)	19015-0001	19015-0002	.802 (20.4)
18-12 AWG (1.0-3.0)	.250 x .032	.180 (4.57)	19015-0003	19015-0004	.802 (20.4)