




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Wire**

Number of Positions: **9**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	9
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	3

Electrical Characteristics

Operating Voltage	300 VAC
Insulation Resistance	1000 MΩ

Contact Features



Contact Layout	Matrix
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	7 A
Contact Retention Within Housing	Without
Contact Type	Receptacle

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Retention	With
Mating Retention Type	Latch

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Nylon 6/6

Dimensions

Row-to-Row Spacing	4.6 mm[.181 in]
Height	16.2 mm[.64 in]
Length	19.3 mm[.76 in]

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire



Packaging Features

Packaging Method	Bag
Packaging Quantity	500

Other

For Use With	Cap Housing
--------------	-------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 175156-2 U/P REC CONT L/P	 TE Part # 175155-1 UNIV POWER REC CONT L/P	 TE Part # 175151-1 AMP UNIVERSAL POWER REC CONT.	 TE Part # 175152-1 UNIVERSAL POWER REC
 TE Part # 175152-2 AMP UNIVE. POWER CONN REC CONT	 TE Part # 175151-2 AMP UNIVE. POWER CONN REC CONT	 TE Part # 175155-2 U/P REC CONT L/P	 TE Part # 175156-1 UNIV POWER REC CONT L/P
 TE Part # 176297-1 UNIV POWER CAP HSG 9P P/MOUNT	 TE Part # 176287-1 AMP UNIVERSAL POWER CAP 9P	 TE Part # 175151-5 AMP UNIVERSAL POWER CONN.REC C	 TE Part # 176287-2 AMP UNIVERSAL POWER CAP 9P
 TE Part # 176287-4 AMP UNIVERSAL POWER CAP 9P	 TE Part # 175151-4 UNIVESAL POWER REC CONT #26-22	 TE Part # 175152-3 UNIV POWER REC CONT	 TE Part # 175152-4 UNIVESAL POWER REC CONT #20-16

Also in the Series | AMP Universal Power

 Connector Contacts(1)	 Insertion & Extraction Tools(1)	 Power Contacts(21)	 Rectangular Power Connectors(177)
--	---	---	--

Customers Also Bought



TE Part #179467-1
AMP POWER DBL LOCK CAP HSG 8P



TE Part #176299-1
UNVI POWER CAP HSG 12P PNL MTG



TE Part #176275-1
UNIV POWER PLUG HSG 8P F/H



TE Part #172131-1
FF 250 REC HSG 3P NYLON NAT



TE Part #176286-1
UNIV POWER CAP HSG 8P F/H



TE Part #170011-8
RING STRIP 18-14 MM2 0.503 X 11.938 TPBR



TE Part #176280-1
UNIV POWER PLUG HSG 18P F/H



TE Part #176277-1
UNIV POWER PLUG HSG 10P F/H



TE Part #171383-1
6 CIRCUIT M-N-L CAP

Documents

Product Drawings

AMP UNIVERSAL POWER PLUG 9P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_176276-1_H.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_176276-1_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_176276-1_H.3d_stp.zip

English

Customer View Model

ENG_CVM_176276-1_B.3d_igs.zip

English



Customer View Model

[ENG_CVM_176276-1_B.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_176276-1_B.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Crimping of Universal Power Contact](#)

English

[Product Specification](#)

Japanese

[AMP Universal Power Connector](#)

Japanese

Instruction Sheets

[AMP UNIVERSAL POWER CONNECTOR SERIES](#)

English

[Instruction Sheet \(non U.S.\)](#)

English

Agency Approvals

[UL Report](#)

English