


Power Double Lock

TE Internal #: 2005247-6 Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, .156 in [3.96 mm] Centerline, Wire & Cable, UL 94V-0, Power Double Lock

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Plug



Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Wire

Number of Positions: 2

Centerline (Pitch): 3.96 mm [.156 in]

All Glow Wire Power Double Lock Plug (55)

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	2
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	1
Electrical Characteristics	
Operating Voltage	50 VAC, 300 VAC

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, .156 in [3.96 mm] Centerline, Wire & Cable, UL 94V-0, Power Double Lock



Contact Features

Contact Layout	Inline	
Contact Retention Within Housing	Without	
Contact Type	Receptacle	
Termination Features		
Termination Method to Wire & Cable	Crimp	
Wire/Cable Type	Discrete Wire	
Wire Type	Stranded	
Mechanical Attachment		
Connector Mounting Type	Cable Mount (Free-Hanging)	
Housing Features		
Centerline (Pitch)	3.96 mm[.156 in]	
Housing Color	Blue	
Housing Material	PA 66	
Usage Conditions		
Operating Temperature Range	-30 – 65 °C[-22 – 149 °F]	

Operation/Application

Circuit Application	Power & Signal	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Glow Wire Rating	GWT 750°C (Without Flame)	
Agency/Standard Number	C22.2 No. 182.3, UL 1977	
Agency/Standard	CNR, USR	
Packaging Features		
Packaging Method	Bag	
Packaging Quantity	500	
Other		
For Use With	Cap (GWT): 2005248 or 2005249, Contacts: 177914 or 177915, Double Lock Plate 177918-1 or (GWT) 368590-1	

Product Compliance

For compliance documentation, visit the product page on TE.com>

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, .156 in [3.96 mm] Centerline, Wire & Cable, UL 94V-0, Power Double Lock



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts




Also in the Series | Power Double Lock

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, .156 in [3.96 mm] Centerline, Wire & Cable, UL 94V-0, Power Double Lock








Customers Also Bought



TE Part #926298-7 UNIVERSAL MATE-N-LOK 4 WAY PLUG	TE Part #1586851-1 02P UMNL PLUG HSG, GW	TE Part #926984-1 STD TIMER CONTACT	TE Part #1971785-1 PTL RECEPTACLE CONTACT, 20 - 24 AWG
Alk			
TE		=TE	
TE Part #1971786-1 PTL TAB CONTACT, 20 - 24 AWG	TE Part #1-1971772-2 PTL 1X2 CAP PANEL MT STD TEMP KEY A NAT	TE Part #3-1241965-2 STD TIMER HOUSING	

Documents



Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2 Position, .156 in [3.96 mm] Centerline, Wire & Cable, UL 94V-0, Power Double Lock



English

Customer View Model ENG_CVM_CVM_2005247-6_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2005247-6_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Product Environmental Compliance MD_2005247-6_091720142157_dmtec

English

MD_2005247-6_091720142157_dmtec

English

Agency Approvals

UL Report

English