



**7.62mm (.300") Pitch  
MX150L™ Sealed  
Wire-to-Wire Plugs,  
Receptacles and Terminals  
8, 10, 12 AWG**

- 19433** Plugs
- 19432** Receptacles
- 19431** Male Terminals
- 19434** Female Terminals

*Additional pitch and wire gauge options enhance Molex's high-performance MX150L connector system, which is designed for challenging, rugged and harsh applications*

The MX150L 8, 10 and 12 AWG additions are designed to meet the need for a rugged, environmentally sealed connector system supporting high-power applications and long-voltage runs to eliminate voltage drops. The new pitch and wire gauge options add to the existing product family of 14 – 22 AWG with a 5.84mm (.230") pitch. The 7.62mm (.300") pitch supports up to 40 amps per circuit.

This innovative mat-sealed connector family is based upon a 2.50mm (.098") blade-type terminal system, available in a pre-Tin finish. This design eliminates the need to purchase, handle and crimp individual wire seals, which lowers applied cost. The mat-seal design is a single silicone-based seal with individual wire openings and a seal cap to protect, securely retain, and provide strain relief to the seal. The cost-effective connector design features all-in-one plug and receptacle housings with pre-assembled mat-wire and interfacial connector seals. Integral terminal position assurance (TPA) and connector position assurance (CPA) components eliminate time-consuming and costly assembly operations. Populating the housings consists

of crimp-and-poke technology. Simply crimp the appropriate terminal, insert the crimped terminal lead, and seat the TPA to it's lock position. No additional components are required.

Tooling solutions include FineAdjust™ crimp press applicators for high-volume production, as well as hand tools for low-volume production and field repairs.



**Features and Benefits**

- Pre-assembled connector housings and TPA components shipped in one-piece units for applied labor and cost savings
- Simple crimp, poke and plug application eliminates need to crimp individual wire seals
- Integral terminal position assurance (TPA) assures that crimped terminal leads are properly locked into connector (TPA will not seat into final lock position and connector system will not latch if terminal is not locked properly into position)
- Integral, two-way mat seal on the mating connector designed and tested to IEC IP 67 exceeds "waterproof" demands as a true sealed connector system tested under submersed conditions in various fluids
- Two independent terminals (10 to 12 AWG and 8 AWG) allow customers to support 30amp applications with 10 to 12 AWG terminals and 40amp applications with 8 AWG terminals
- Audible and tactile feedback clicks on insertion, extraction and mating facilitates reliable mating and terminal loading and removal
- 7.62mm (.300") pitch housing design with 2 styles of terminals for wire styles from 10 to 12 AWG as well 8 AWG allows flexibility in selecting from a wide range of wire styles and insulation thicknesses, (nominal O.D. ranges .155 to .237") to support numerous applications

**SPECIFICATIONS**

**Reference Information**

Packaging:  
Housings — Bulk  
Terminals — Reel and loose piece  
UL File No.: E152602  
Designed In: Inches

**Electrical**

Voltage: 600V  
Current: 10 to 12 AWG — 30.0A  
8 AWG — 40.0A  
Dielectric Withstanding Voltage: 2200V AC min.  
Insulation Resistance: 1000 Megohms

**Mechanical**

Contact Insertion Force: 4.4N (1 lbf) max.  
Sealing: IEC 529 — IP67 standard  
Durability: 25 cycles

**Physical**

Housing: Glass-filled PBT, Black  
Contact: Copper (Cu) Alloy  
Plating: Tin (Sn)  
Operating Temperature: -40 to +125°C  
Flammability: UL 94V-0

## APPLICATIONS

- Agriculture equipment
- Construction equipment
- Recreational vehicles
- Marine equipment




**7.62mm (.300")  
PitchMX150L™ Sealed  
Wire-to-Wire Plugs,  
Receptacles and Terminals  
8, 10, 12 AWG**


**19433 Plugs  
19432 Receptacles  
19431 Male Terminals  
19434 Female Terminals**

## ORDERING INFORMATION


### Female Terminals

 10-12 AWG      8 AWG	AWG	Insulation Diameter mm (in)	Order No.		Dimensions mm (in)			
			Loose	Strip	A	B	C	D
	10-12	3.94-4.45 (.155-.175)	19434-0003	19434-0001	6.35 (.250)	6.00 (.236)	5.00 (.197)	5.60 (.220)
	8	6.02 (.237)	19434-0004	19434-0002	N/A	N/A	6.10 (.240)	7.0 (.276)


### Male Terminals

 10-12 AWG      8 AWG	AWG	Insulation Diameter mm (in)	Order No.		Dimensions mm (in)			
			Loose	Strip	A	B	C	D
	10-12	3.94-4.45 (.155-.175)	19431-0016	19431-0001	6.35 (.250)	6.00 (.236)	5.00 (.197)	5.60 (.220)
	8	6.02 (.237)	19431-0017	19431-0015	N/A	N/A	6.10 (.240)	7.00 (.276)


### Single-Row Receptacle

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19432-0013	2	10-12	Yellow
	19432-0014		8	Red


### Single-Row Plug

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19433-0013	2	10-12	Yellow
	19433-0014		8	Red

### Dual-Row Receptacle - 8, 10, 12 AWG

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19432-0001	4	10-12	Yellow
	19432-0002		8	Red

### Dual-Row Plug - 8, 10, 12 AWG

	Order No.	Circuits	Wire Range (AWG)	Mat Seal Color
	19433-0001	4	10-12	Yellow
	19433-0002		8	Red

**Americas Headquarters**  
Lisle, Illinois 60532 U.S.A.  
1-800-78MOLEX  
amerinfo@molex.com

**Far East North Headquarters**  
Yamato, Kanagawa, Japan  
81-462-65-2324  
feninfo@molex.com

**Far East South Headquarters**  
Jurong, Singapore  
65-6-268-6868  
fesinfo@molex.com

**European Headquarters**  
Munich, Germany  
49-89-413092-0  
eurinfo@molex.com

**Corporate Headquarters**  
2222 Wellington Ct.  
Lisle, IL 60532 U.S.A.  
630-969-4550  
Fax: 630-969-1352

Visit our website at [www.molex.com/mx150Lsealedwtw.html](http://www.molex.com/mx150Lsealedwtw.html)