2-179553-4 - ACTIVE

Dynamic Series | Dynamic 3000 Series

TE Internal #: 2-179553-4 Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, 5.08 mm [.2 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Dynamic 3000 Series

View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings >

Receptacle and Tab Housing: 5.08 mm pitch, 250-600V



Connector Product Type: Housing Connector & Housing Type: Housing for Male Terminals Connector System: Wire-to-Wire Number of Positions: 4 Centerline (Pitch): 5.08 mm [.2 in]

All Receptacle and Tab Housing: 5.08 mm pitch, 250-600V (64)

Features

Product Type Features



Connector Product Type	Housing							
Connector & Housing Type	Housing for Male Terminals							
Connector System	Wire-to-Wire							
Sealable	No							
Connector & Contact Terminates To	Wire & Cable							
Configuration Features								
Number of Positions	4							
Number of Rows	1							
Termination Features								
Termination Method to Wire & Cable	Crimp							
Mechanical Attachment								
Mating Retention	With							
Connector Mounting Type	Panel Mount							
Housing Features								
Centerline (Pitch)	5.08 mm[.2 in]							

Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, 5.08 mm [.2 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Dynamic 3000 Series



Housing Color	Black				
Usage Conditions					
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]				
Operation/Application					
Circuit Application	Power & Signal				
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant				
EU ELV Directive 2000/53/EC	Compliant				
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold				
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed				
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.				
Solder Process Capability	Not applicable for solder process capability				

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach


Compatible Parts

Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, 5.08 mm [.2 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Dynamic 3000 Series




TE Part # CAT-D9934-A75 Contact: Component To Wire; 15A, 28-14 wire size

Also in the Series | Dynamic 3000 Series



PCB Headers & Receptacles(283)	PCB Terminal Blocks(25)	Standard Rectangular Connectors(2)	Wire-to-Board Connector Assemblies
			& Housings(152)



Customers Also Bought



Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, 5.08 mm [.2 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Dynamic 3000 Series





Documents

Product Drawings DYNAMIC D-3200S TAB HSG 4P K/Y

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_2-179553-4_R.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-179553-4_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-179553-4_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the $\ensuremath{\text{Terms}}$ and $\ensuremath{\text{Conditions}}$ of use.

Datasheets & Catalog Pages 1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

Japanese

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

English

Product Specifications

Product Specification

English

Product Environmental Compliance MD_2-179553-4_062020111142

English

MD_2-179553-4_062020111142

English

Instruction Sheets

Instruction Sheet (U.S.)

& For support call+1 800 522 6752

Housing, Housing for Male Terminals, Wire-to-Wire, 4 Position, 5.08 mm [.2 in] Centerline, Crimp, 1 Row, Black, Mating Retention, Dynamic 3000 Series



English
Agency Approvals
TUV Certificate
English