



# STANDARD RECTANGULAR CONNECTORS



TE CONNECTIVITY (TE)

## METRIMATE PIN HEADER ASSY,3P

AMP | Metrimate

207541-3

TE Internal Number: 207541-3

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Polarization**

Mating Retention **With**

Mating Retention Type **Locking Latch**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

### Product Drawings

[PIN HEADER ASSEMBLY, 3 POSN, IN-LINE, RIGHT ANGLE, SMALL METRIC CONNECTOR, METRIMATE](#)

PDF (TIFF AVAILABLE)  
English

[PIN HEADER ASSEMBLY, 3 POSN, IN-LINE, RIGHT ANGLE, SMALL METRIC CONNECTOR, METRIMATE](#)

PDF (TIFF AVAILABLE)  
English

### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

### Product Specifications

Application Specification

[Metrimate Self-Locking Connectors](#)

PDF  
English

[METRIMATE Self-Locking Connectors](#)

TIF  
Japanese

[METRIMATE Self-Locking Connectors](#)

PDF  
Japanese

### Product Environmental Compliance

TE Material Declaration

[MD\\_207541-3\\_102820141030\\_dmtec](#)

PDF

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	<b>Connector</b>
	PCB Mounting Orientation	<b>Right Angle</b>
	Connector System	<b>Wire-to-Board</b>
	Connector Style	<b>Receptacle</b>
	Connector Type	<b>Header</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>3</b>
	Number of Rows	<b>1</b>
	Connector Configuration	<b>Inline</b>

---

Electrical Characteristics	Operating Voltage	<b>600 VAC [ 600 VDC ]</b>
----------------------------	-------------------	----------------------------

---

Contact Features	Contact Current Rating (A)	<b>7.5</b>
	Contact Type	<b>Pin</b>
	Tail Plating Material	<b>Tin-Lead</b>
	Contact Transmits (Typical)	<b>Signal (Data)</b>
	Contact Layout	<b>Inline</b>

---

Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
----------------------	--------------------------------	------------------------------

---

Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Locking Latch</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Mounting Holes</b>

---

Housing Features	Centerline	<b>5 mm [ .197 in ]</b>
	Housing Material	<b>Nylon GF</b>
	Housing Color	<b>Red</b>

---

Dimensions	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Tail Length	<b>4.88 mm [ .192 in ]</b>
	Width (mm)	<b>17.5</b>
	Length (mm)	<b>36.86</b>
	Height (mm)	<b>12.7</b>
<hr/>		
Usage Conditions	Operating Temperature Range	<b>-55 – 130 °C [ -67 – 266 °F ]</b>
<hr/>		
Operation/Application	For Use With	<b>Plug Housing</b>
<hr/>		
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA File Number	<b>LR16455</b>
	VDE Tested	<b>Yes</b>
	UL Rating	<b>Certified, Recognized</b>
	Agency/Standard	<b>CSA, UL</b>
	UL File Number	<b>E28476</b>
<hr/>		
Packaging Features	Packaging Quantity	<b>14</b>
	Packaging Method	<b>Tube, Tube/Box</b>
<hr/>		
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	