

VAL-U-LOK

TE Internal #: 2029265-4 Rectangular Power Connectors, Header, Plug, Wire-to-Board, 4 Position, .165 in [4.2 mm] Centerline, Printed Circuit Board, UL 94V-0 View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header

Connector & Housing Type: Plug

Connector System: Wire-to-Board

Number of Positions: **4**

Centerline (Pitch): 4.2 mm [.165 in]

Features

Product Type Features

Rectangular Power Connector Type	Header	
Connector & Housing Type	Plug	
Connector System	Wire-to-Board	
Sealable	No	
Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Number of Positions	4	
PCB Mount Orientation	Vertical	
Number of Power Positions	4	
Number of Rows	2	
Electrical Characteristics		
Operating Voltage	600 VAC	
Contact Features		
Contact Layout	Inline	

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 4 Position, .165 in [4.2 mm] Centerline, Printed Circuit Board, UL 94V-0



Multiple Contact Types	With	
Contact Current Rating (Max)	9 A	
Contact Retention Within Housing	Without	
Contact Type	Pin	
PCB Contact Termination Area Plating Material	Tin	
Contact Mating Area Plating Material	Tin	
Termination Features		
Termination Post & Tail Length	3.5 mm[.138 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	
Mechanical Attachment		
Mating Alignment Type	Keyed	
Mating Alignment	With	
PCB Mount Alignment	With	
PCB Mount Retention	With	
PCB Mount Retention Type	Boardlock	
Connector Mounting Type	Board Mount	
Mating Retention	With	

Mating Retention Type

Latch

Housing Features

Centerline (Pitch)	4.2 mm[.165 in]	
Housing Color	Natural	
Housing Material	Polyamide	
Dimensions		
Row-to-Row Spacing	4.2 mm[.165 in]	
PCB Thickness (Recommended)	.7 mm[1.78 in]	
Width	9.75 mm[.384 in]	
Accepts Wire Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]	
Height	12.8 mm[.504 in]	
Length	9.6 mm[.38 in]	
Usage Conditions		
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]	
Operation/Application		

C For support call+1 800 522 6752

07/23/2022 10:44AM | Page 2

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 4 Position, .165 in [4.2 mm] Centerline, Printed Circuit Board, UL 94V-0



Circuit Application	Power	
Identification Marking		
Circuit Identification Feature	With	
Industry Standards		
UL Flammability Rating	UL 94V-0	
Glow Wire Rating	GWT 750°C (Without Flame)	
Agency/Standard Number	E28476	
Agency/Standard	CSA, UL	
UL Rating	Recognized	
CSA File Number	208567	
Packaging Features		
Packaging Method	Box & Tray, Tray	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 4 Position, .165 in [4.2 mm] Centerline, Printed Circuit Board, UL 94V-0



Compatible Parts



TE Part # 1586862-4 4P FH PLUG VAL-U-LOK FH GW




TE Part # 1586861-4 4P PM PLUG VAL-U-LOK PM GW



TE Part # 2296206-4 4P FH PLUG VAL-U-LOK FH GWT/V0



TE Part # 2296207-4 4P PM PLUG VAL-U-LOK PM GWT/V0



Customers Also Bought



TE Part #5-103634-7	TE Part #1877285-3	TE Part #5745171-5	TE Part #3-1415899-7
08 MTE HDR SRRA LATCH.100CL LF	03P EP SHRD HDR ASMY, WHITE	AMPL CBL CLMP KIT SZ 1	RZ01-1A3-D005
TE Part #1-188685-2	TE Part #1744057-9	TE Part #NB15492001	TE Part #1-2071448-8
STD TIMER PCB CONTACT	3.96 EP HDR ASSY 9P W/PEGS	RNF-100-3/64-BK-STK	ORWH-SS-124DM1F,000



Rectangular Power Connectors, Header, Plug, Wire-to-Board, 4 Position, .165 in [4.2 mm] Centerline, Printed Circuit Board, UL 94V-0



Documents

Product Drawings 4P VAL-U-LOK VRTHDR W/PGS GW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2029265-4_D_c-2029265-4-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2029265-4_D_c-2029265-4-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2029265-4_D_c-2029265-4-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages VAL-U-LOK_GLOW_WIRE_CONNECTORS

English

Product Environmental Compliance MD_2029265-4_101120182347_dmtec

English

MD_2029265-4_101120182347_dmtec

English

Agency Approvals UL Report

English