SOLISTRAND

TE Internal #: 2-33460-2

Ring Terminals & Spade Terminals, Ring Tongue, 8 AWG Wire Size,

8 mm² Wire Size, 13100 – 20800 CMA Wire Size, Stud Size #10

View on TE.com >



Terminals & Splices > Ring Terminals & Spade Terminals











Ring & Spade Terminal Type: Ring Tongue

Wire Size: 13100 – 20800 CMA

Stud Size: #10

Features

Product Type Features

Froduct Type realures			
Shape Description	RING-049		
Stud Size	#10		
Sealable	No		
Wire Insulation Support Retention Type	Non-Insulation Support		
Configuration Features			
Number of Holes	1		
Terminal Angle	180°		
Body Features			
Inspection Slot	No		
Weight per Piece	3.426 g		
Contact Features			
Ring & Spade Terminal Type	Ring Tongue		
Barrel Type	Closed		

Offset

Tin

Mechanical Attachment

Terminal Orientation

Terminal Plating Material



Wire Insulation Support	Without
Dimensions	
Wire Size	13100 – 20800 CMA
Stud Diameter	5 mm[.197 in]
Tongue Thickness	.79 mm[.031 in]
Overall Product Length	23.7 mm[.933 in]
Barrel Inside Diameter	4.37 mm[.172 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Heavy Duty	No
Industry Standards	
Government Qualified	No
Packaging Features	
Packaging Quantity	1500
Packaging Method	Tape Mounted
Other	
Comment	Requires a 69875 standard TAPETRONIC machine for application., Tape mounted on 15.24 [.600] centers.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold:



	\ / .	ъ.	
100	Yet	Review	0

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free


Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought























Documents

Product Drawings

TERMINAL, SOLIS R 8 10

English

CAD Files

Customer View Model

ENG_CVM_CVM_2-33460-2_V.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-33460-2_V.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-33460-2_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals

UL Report

English